


# Technical Data Sheet

## NESSOL 40



1/1/2020

Properties	Unit	Specification		Test Method*
		min	max	
Aromatic content	% v/v	13	20	EN 12916
Benzene content	mg/l	85.0	-	NM 111
Flash Point, APcc	°C	39	-	DIN 51755
Distillation, initial boiling point	°C	150	-	EN ISO 3405
Sulphur content	mg/kg	-	3.0	EN ISO 20846
Copper strip corrosion		-	1b	EN ISO 2160
Doctor test		-	Negat.	ASTM D 4952
Colour, Saybolt		+30	-	ASTM D 6045
Appearance		Clear and Bright		D 4176-1

The Solvent Emission Directive (EU Directive 1999/13/EC) limits emissions of Volatile Organic Compounds (VOCs). This directive defines a VOC as any organic compound having a vapour pressure of 0.01 kPa or more at + 293.15 K (+ 20 °C). Vapour pressure of Nessol 40 at + 20 °C is > 0.01 kPa, measured.

The product will comply with the specification according to the procedures described in ISO 4259.

Concerning safe use of the products, we refer to the Safety Data Sheets and User's Guides published by Neste Oyj.

#### INQUIRIES

Neste Retail

POB 95

FIN-00095 Neste Oyj, Finland

Telephone +358 20 80100