

# **NESTE PRO GEAR V 75W-80**

**Fully synthetic gear oil for heavy duty vehicles with extended drain**

## **PERFORMANCE CLAIMS**

**API: GL-4**

**SAE 75W-80**

**MAN 341 Type E4**

**MAN 341 Type VR**

**MB 235.29**

**Volvo 97307**

**EATON Manual Transmission**

**Voith Retarder 153.0009001**

## **DESCRIPTION**

**Neste Pro Gear V 75W-80 is an advanced fully synthetic gear oil. Developed especially to keep its performance also with extended drain. Applies also for Volvo i-Shift gear boxes with 200 000 km/36 months drain interval.**

## **SPECIAL FEATURES AND BENEFITS**

- advanced additives give superb protection against corrosion, oxidation and foaming**
- top class base oils and carefully chosen additives gives a long working life**
- Because of fully synthetic base oils, Neste Pro Gear V 75W-80 is suitable for use in wide temperature range.**

## **TYPICAL CHARACTERISTICS**

|                                       |                   |
|---------------------------------------|-------------------|
| <b>Density kg/m<sup>3</sup> 15 °C</b> | <b>861</b>        |
| <b>Flash Point °C (COC)</b>           | <b>220</b>        |
| <b>Pour Point °C</b>                  | <b>-55</b>        |
| <b>Viscosity Index</b>                | <b>144</b>        |
| <b>Viscosity cSt/ 40 °C</b>           | <b>65</b>         |
| <b>Viscosity cSt/ 100 °C</b>          | <b>10,2</b>       |
| <b>Viscosity cP/ °C</b>               | <b>2E+0 / -40</b> |
|                                       | <b>5</b>          |

## **APPLICATIONS**

**Neste Pro Gear V is suitable for many transmission manufacturer by European, Asian and North American OEMs, for example Irisbus, Iveco, Mack, MAN, Renault, Sisu ja Volvo, if the product meets the requirements.**

**Also recommended for use also if API: GL-4 SAE 75W-80 gear oil is required.**

**31.3.2017**