



SAFETY DATA SHEET NESSOL D60E

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name	NESSOL D60E
Product number	ID 10565
Internal identification	137511, 137520
Synonyms; trade names	Previous product name: NESSOL LIAV 230E. Previous product number: 756511, 756520.

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses	Solvent. Use in cleaning agents
-----------------	---------------------------------

1.3. Details of the supplier of the safety data sheet

Supplier

Neste Markkinointi Oy
Keilaranta 21, Espoo, PL 95, FIN-00095 NESTE, FINLAND
Tel. +358 10 45811
fueltec@neste.com

1.4. Emergency telephone number

National emergency telephone number +358-9-471 977, +358-9-4711, Poison Information Centre

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards	Not Classified
Health hazards	Asp. Tox. 1 - H304
Environmental hazards	Not Classified

2.2. Label elements

Pictogram



Signal word	Danger
Hazard statements	H304 May be fatal if swallowed and enters airways.
Precautionary statements	P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor. P331 Do NOT induce vomiting. P501 Dispose of contents/ container in accordance with national regulations.
Supplemental label information	EUH066 Repeated exposure may cause skin dryness or cracking.

NESSOL D60E

Contains Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics

2.3. Other hazards

Other hazards Combustible liquid., Evaporates slowly., Vapours may irritate throat/respiratory system., Risk of soil and ground water contamination.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics	97 %
CAS number: —	REACH registration number: 01-2119457273-39-XXXX
Classification Asp. Tox. 1 - H304	

(2-methoxymethylethoxy)propanol	< 1 %
CAS number: 34590-94-8	EC number: 252-104-2
	REACH registration number: 01-2119450011-60-XXXX
Classification Not Classified	

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

Other information Total aromatics at maximum:, 1 vol-%.
Identity outside the EU (CAS number and name of the substance):, 64742-48-9, Naphtha (petroleum), hydrotreated heavy, Previous EC number:, 265-150-3

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation Remove person to fresh air and keep comfortable for breathing. Get medical attention if symptoms are severe or persist.

Ingestion Do not induce vomiting. Get medical attention immediately.

Skin contact Remove contaminated clothing immediately and wash skin with soap and water. Get medical attention if irritation persists after washing.

Eye contact Rinse immediately with plenty of water. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation persists after washing.

4.2. Most important symptoms and effects, both acute and delayed

General information Repeated exposure may cause skin dryness or cracking. Entry into the lungs following ingestion or vomiting may cause chemical pneumonitis.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media Water spray, foam, dry powder or carbon dioxide.

NESSOL D60E

Unsuitable extinguishing media Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Specific hazards Combustible liquid. Containers can burst violently or explode when heated, due to excessive pressure build-up.

Hazardous combustion products Carbon dioxide (CO₂). Carbon monoxide (CO).

5.3. Advice for firefighters

Protective actions during firefighting Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk. Prevent fire extinguishing water from contaminating surface water or the ground water system.

Special protective equipment for firefighters Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Avoid inhalation of vapours and contact with skin and eyes. Wear adequate protective equipment at all operations.

For non-emergency personnel Keep upwind to avoid inhalation of gases, vapours, fumes and smoke.

For emergency responders Prevent unauthorized access. Use only in well-ventilated areas.

6.2. Environmental precautions

Environmental precautions Avoid release to the environment. Stop leak if safe to do so. Avoid the spillage or runoff entering drains, sewers or watercourses. Inform the relevant authorities if environmental pollution occurs (sewers, waterways, soil or air). Risk of soil and ground water contamination.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Immediately start clean-up of the liquid and contaminated soil. Large spills should be collected mechanically (remove by pumping) for disposal. Small Spillages: Absorb spillage with sand or other inert absorbent. Pay attention to the fire and health hazards caused by the product.

6.4. Reference to other sections

Reference to other sections For personal protection, see Section 8. For waste disposal, see Section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions This material is a static accumulator. Avoid heat, flames and other sources of ignition. Take precautionary measures against static discharges. All handling should only take place in well-ventilated areas. Try to avoid product volatilization during handling and transferring. Avoid inhalation of vapours and contact with skin and eyes. Use personal protective equipment and/or local ventilation when needed. Do not eat, drink or smoke when using this product. Wash hands and any other contaminated areas of the body with soap and water before leaving the work site. During tank operations follow special instructions (risk of oxygen displacement and hydrocarbons).

7.2. Conditions for safe storage, including any incompatibilities

NESSOL D60E

Storage precautions Flammable liquid storage. Store in accordance with local regulations. Keep container tightly closed, in a cool, well ventilated place. Keep away from food, drink and animal feeding stuffs. Store in a demarcated bunded area to prevent release to drains and/or watercourses. Take precautions against leakage by constructing collecting pools and sewerage systems as well as by surfacing the loading and unloading stations. Suitable container materials: Stainless steel. Carbon steel. Polytetrafluoroethylene (PTFE, Teflon). Polypropylene Polyethylene. Unsuitable container materials: Butyl rubber. Rubber (natural, latex). EPDM (ethylene-propylene-diene monomer). Polystyrene

7.3. Specific end use(s)

Specific end use(s) Not known.

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

Occupational exposure limits

(2-methoxymethylethoxy)propanol

(2-methoxymethylethoxy)propanol: 50 ppm (8h), 310 mg/m³ (8h), HTP 2016/FIN, EU OELV (EC/2000/39)

May be absorbed through the skin.

Ingredient comments Solvent naphtha, group 1: 500 mg/m³ (8h), HTP 2016/FIN. The individual limit values can be applied for the hydrocarbons.

DNEL Hydrocarbons:
C10-C13
DNEL derivation is not justified.

PNEC Not available.

8.2. Exposure controls

Appropriate engineering controls All handling should only take place in well-ventilated areas. Use personal protective equipment and/or local ventilation when needed. Handle in accordance with good industrial hygiene and safety practice.

Eye/face protection Tight-fitting safety glasses.

Hand protection Wear protective gloves. It is recommended that gloves are made of the following material: Nitrile rubber. Neoprene. The selected gloves should have a breakthrough time of at least 4 hours. Protection class 5. Protective gloves according to standards EN 420 and EN 374. Change protective gloves regularly.

Other skin and body protection Protective clothing when needed. Wear anti-static protective clothing if there is a risk of ignition from static electricity.

Respiratory protection Filter device/half mask Gas filter, type A2. Filter device could be used maximum 2 hours at a time. Filter devices must not be used in conditions where the oxygen level is low (< 19 vol.-%). At high concentrations a breathing apparatus must be used (self-contained or fresh air hose breathing apparatus). Filter must be changed often enough. Respirators according to standards EN 140 and EN 141.

Environmental exposure controls Take precautions against leakage by constructing collecting pools and sewerage systems as well as by surfacing the loading and unloading stations.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Appearance Mobile liquid.

Colour Clear.

NESSOL D60E

Odour	Hydrocarbons. Mild.
Odour threshold	-
pH	-
Melting point	< -15°C Pour point
Initial boiling point and range	175...225°C (EN ISO 3405)
Flash point	≥ 61°C (EN ISO 2719)
Upper/lower flammability or explosive limits	Lower flammable/explosive limit: ~0,6 % (calculated) Upper flammable/explosive limit: ~7 % (calculated)
Vapour pressure	< 1 kPa @ 38°C
Vapour density	> 3 (Air = 1.0)
Relative density	~ 0,8 @ 15/4°C (ISO 12185)
Solubility(ies)	Emulsifiable in water.
Partition coefficient	log Kow: 3... > 6
Auto-ignition temperature	> 200°C Estimated value.
Decomposition Temperature	-
Viscosity	Kinematic viscosity Hydrocarbons: C10-C13; < 7 mm ² /s @ 40°C (EN ISO 3104) (2-methoxymethylethoxy)propanol: 5.14
Explosive properties	Not considered to be explosive.
Oxidising properties	Does not meet the criteria for classification as oxidising.
<u>9.2. Other information</u>	
Other information	Not known.

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity There are no known reactivity hazards associated with this product.

10.2. Chemical stability

Stability Stable at normal ambient temperatures and when used as recommended.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions No potentially hazardous reactions known.

10.4. Conditions to avoid

Conditions to avoid Keep away from heat, sparks and open flame. Take precautionary measures against static discharges.

10.5. Incompatible materials

Materials to avoid Oxidising agents.

10.6. Hazardous decomposition products

Hazardous decomposition products None known.

NESSOL D60E

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Toxicological effects	Based on available data the classification criteria are not met.
<u>Skin corrosion/irritation</u>	
Skin corrosion/irritation	Based on available data the classification criteria are not met., Repeated exposure may cause skin dryness or cracking., Hydrocarbons:, C10-C13: OECD 404, HRIPT = Human Repeated Insult Patch Test
<u>Serious eye damage/irritation</u>	
Serious eye damage/irritation	Based on available data the classification criteria are not met. Hydrocarbons: C10-C13: OECD 405
<u>Skin sensitisation</u>	
Skin sensitisation	Based on available data the classification criteria are not met. Hydrocarbons: C10-C13: OECD 406
<u>Germ cell mutagenicity</u>	
Genotoxicity - in vitro	Based on available data the classification criteria are not met. Hydrocarbons: C10-C13: OECD 471, 473, 476, 479
Genotoxicity - in vivo	Based on available data the classification criteria are not met. Hydrocarbons: C10-C13: OECD 474, 478
<u>Carcinogenicity</u>	
Carcinogenicity	Based on available data the classification criteria are not met. Hydrocarbons: C10-C13: OECD 453
<u>Reproductive toxicity</u>	
Reproductive toxicity - fertility	Based on available data the classification criteria are not met. Hydrocarbons: C10-C13: OECD 413, 415
Reproductive toxicity - development	Based on available data the classification criteria are not met. Hydrocarbons: C10-C13: OECD 414
<u>Specific target organ toxicity - single exposure</u>	
STOT - single exposure	Not classified as a specific target organ toxicant after a single exposure.
<u>Specific target organ toxicity - repeated exposure</u>	
STOT - repeated exposure	Based on available data the classification criteria are not met. Hydrocarbons: C10-C13: OECD 408, 413, 422
<u>Aspiration hazard</u>	
Aspiration hazard	May be fatal if swallowed and enters airways. Entry into the lungs following ingestion or vomiting may cause chemical pneumonitis.

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Acute toxicity - oral

Notes (oral LD₅₀) LD₅₀ > 5000 mg/kg, Oral, Rat (OECD 401, 423)

Acute toxicity - dermal

Notes (dermal LD₅₀) LD₅₀ > 3000 mg/kg, Dermal, Rabbit LD₅₀ > 2000 mg/kg, Dermal, Rat (OECD 402)

Acute toxicity - inhalation

Notes (inhalation LC₅₀) LC₅₀ > 5000 mg/m³, Inhalation, Rat (4h) (OECD 403)

NESSOL D60E**(2-methoxymethylethoxy)propanol****Acute toxicity - oral**Notes (oral LD₅₀) LD₅₀ > 2000 mg/kg, Oral, Rat**SECTION 12: Ecological Information****12.1. Toxicity**

Toxicity Based on available data the classification criteria are not met.

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Acute toxicity - fish	LL ₅₀ , 96 hours: > 1000 mg/l, LL0, 96 hours: 1000 mg/l, (OECD 203)
Acute toxicity - aquatic invertebrates	LL ₅₀ , 48 hours: > 1000 mg/l, LL0, EL0, 48 hours: 1000 mg/l, (OECD 202) LL ₅₀ , 96 hours: > 1000 mg/l, Marine water NOELR, 96 hours: 32 mg/l, Marine water (EPA OPPTS 850.1020)
Acute toxicity - aquatic plants	EL50, 72 hours: > 1000 mg/l, Fish NOELR, 72 hours: 1000 mg/l, Fish (OECD 201)
Acute toxicity - microorganisms	EL50, 48 hours: > 1000 mg/l, (QSAR)
Chronic toxicity - fish early life stage	NOELR, 28 days: 0,101 mg/l, (QSAR)
Chronic toxicity - aquatic invertebrates	NOELR, 21 days: 0,176 mg/l, (QSAR)

(2-methoxymethylethoxy)propanol

Acute toxicity - fish	LC ₅₀ , 96 hours: > 1000 mg/l, Algae
Acute toxicity - aquatic plants	EC ₅₀ , 96 hours: 969 mg/l, Fish

12.2. Persistence and degradability

Phototransformation	The product contains volatile substances which may spread in the atmosphere. Can be photodegraded in the atmosphere.
Stability (hydrolysis)	No significant reaction in water.

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Biodegradation	Rapidly degradable (OECD 301F)
-----------------------	-----------------------------------

(2-methoxymethylethoxy)propanol

Biodegradation	> 60% BOD, 28d (OECD 301F)
-----------------------	----------------------------

NESSOL D60E

12.3. Bioaccumulative potential

Bioaccumulative potential No data available.

Partition coefficient log Kow: 3... > 6

12.4. Mobility in soil

Mobility Hydrocarbons: C10-C13: Evaporates slowly. Product can penetrate soil until reaching the surface of ground water. The product contains substances which are bound to particulate matter and are retained in soil.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment Hydrocarbons: C10-C13: This product does not contain any substances classified as PBT or vPvB. (2-methoxymethylethoxy)propanol: No information available.

12.6. Other adverse effects

Other adverse effects Not known.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information Waste is classified as hazardous waste.

Disposal methods Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority. When handling waste, the safety precautions applying to handling of the product should be considered. Care should be taken when handling emptied containers that have not been thoroughly cleaned or rinsed out. Waste packaging should be collected for reuse or recycling.

SECTION 14: Transport information

General The product is not covered by international regulations on the transport of dangerous goods (IMDG, IATA, ADR/RID).

14.1. UN number

UN No. (ADR/RID) -

14.2. UN proper shipping name

Proper shipping name (ADR/RID) -

14.3. Transport hazard class(es)

ADR/RID class -

14.4. Packing group

ADR/RID packing group -

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant
No.

14.6. Special precautions for user

Not applicable.

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

NESSOL D60E

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended).
 Commission Regulation (EU) No 2015/830 of 28 May 2015.
 Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).

15.2. Chemical safety assessment

Hydrocarbons: C10-C13: A chemical safety assessment has been carried out.

SECTION 16: Other information

Abbreviations and acronyms used in the safety data sheet DNEL = Derived No-Effect Level
 PNEC = Predicted No-Effect Concentration

Key literature references and sources for data Regulations, databases, literature, own research. Chemical Safety Report Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics.

Revision comments Updated, sections: 1-2, 9, Exposure scenarios Product name change.

Revision date 03/11/2017

Supersedes date 23/10/2017

SDS number 5671

Hazard statements in full H304 May be fatal if swallowed and enters airways.

Exposure scenario

Cleaning - Professional

Identification

Product name Solvent, Heavy deaeromatized - Category 8

Version number N - 2017

1. Title of exposure scenario

Main title Cleaning - Professional

Environment

Environmental release category ERC8a Wide dispersive indoor use of processing aids in open systems.
ERC8d Wide dispersive outdoor use of processing aids in open systems.

Worker

Process category PROC1 Use in closed process, no likelihood of exposure.
PROC2 Use in closed, continuous process with occasional controlled exposure
PROC3 Use in closed batch process (synthesis or formulation).
PROC4 Use in batch and other process (synthesis) where opportunity for exposure arises.
PROC8a Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities.
PROC8b Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities.
PROC10 Roller application or brushing of adhesive and other coating.
PROC11 Spraying outside industrial settings and/or applications.
PROC13 Treatment of articles by dipping and pouring.

2. Conditions of use affecting exposure (Industrial - Environment 1)

Control of environmental exposure

No exposure assessment presented for the environment. The product components are not classified as environmentally hazardous.

2. Conditions of use affecting exposure (Workers - Health 1)

Risk management measures

Avoid splashing.
Avoid contact with contaminated tools and objects.
Avoid contact with eyes and prolonged skin contact.
Handle in accordance with good industrial hygiene and safety practice.
Assumes a good basic standard of occupational hygiene is implemented.

If repeated and/or prolonged skin exposure to the substance is likely, then wear suitable gloves tested to EN374 and provide employee skin care programmes.

Additional advice Do not ingest. If swallowed, then seek immediate medical assistance.

3. Exposure estimation (Health 1)

Qualitative approach used to conclude safe use.

Exposure scenario Cleaning - Consumer

Identification

Product name Solvent, Heavy dearomatized - Category 8

Version number N - 2017

1. Title of exposure scenario

Main title Cleaning - Consumer

Product category PC3 Air care products.
PC4 Anti-freeze and de-icing products.
PC8 Biocidal products.
PC9a Coatings and paints, thinners, paint removers.
PC9b Fillers, putties, plasters, modelling clay.
PC9c Finger paints.
PC24 Lubricants, greases and release products.
PC35 Washing and cleaning products (including solvent-based products).
PC38 Welding and soldering products, flux products.

Environment

Environmental release category ERC8a Wide dispersive indoor use of processing aids in open systems.
ERC8d Wide dispersive outdoor use of processing aids in open systems.

2. Conditions of use affecting exposure (Non-industrial - Environment 1)

Control of environmental exposure (Non-industrial)

No exposure assessment presented for the environment. The product components are not classified as environmentally hazardous.

2. Conditions of use affecting exposure (Non-industrial - Health 1)

Other given operational conditions affecting Non-industrial exposure

Consumer information Do not ingest. If swallowed, then seek immediate medical assistance.

Avoid contact with eyes and prolonged skin contact. No specific risk management measure identified beyond those operational conditions stated.

3. Exposure estimation (Health 1)

Qualitative approach used to conclude safe use.