



## SAFETY DATA SHEET

### Neste Tempora Non-Road Diesel; Neste Pro Non-Road Diesel; MGODMA; DMA Barge

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

##### 1.1. Product identifier

<b>Product name</b>	Neste Tempora Non-Road Diesel; Neste Pro Non-Road Diesel; MGODMA; DMA Barge
<b>Product number</b>	ID 13779
<b>Internal identification</b>	160041, 160051, 160055, 160061, 160071; 160350, 160360, 160370, 160205, 160216; 160364; 160670; 160376, 160377, 160361, 160207, 160215
<b>Synonyms; trade names</b>	Previous product name: Diesel for non-road use; Neste light fuel oil for heating and non-road use; MGODMA; DMA Barge

##### 1.2. Relevant identified uses of the substance or mixture and uses advised against

<b>Identified uses</b>	Distribution of substance, (ES01b) Use as a fuel, (ES12a, ES12b, ES12c)
------------------------	---

##### 1.3. Details of the supplier of the safety data sheet

<b>Supplier</b>	Neste Oyj Keilaranta 21, Espoo, P.O.B. 95, FIN-00095 NESTE, FINLAND Tel. +358 10 45811 SDS@neste.com (chemical safety)
-----------------	---

##### 1.4. Emergency telephone number

<b>National emergency telephone number</b>	+358-9-471 977, +358-9-4711, Poison Information Centre
--	--

#### SECTION 2: Hazards identification

##### 2.1. Classification of the substance or mixture

###### Classification (EC 1272/2008)

<b>Physical hazards</b>	Flam. Liq. 3 - H226
<b>Health hazards</b>	Acute Tox. 4 - H332 Skin Irrit. 2 - H315 Carc. 2 - H351 STOT RE 2 - H373 Asp. Tox. 1 - H304
<b>Environmental hazards</b>	Aquatic Chronic 2 - H411

##### 2.2. Label elements

###### Hazard pictograms



<b>Signal word</b>	Danger
--------------------	--------

<b>Hazard statements</b>	H226 Flammable liquid and vapour. H304 May be fatal if swallowed and enters airways. H315 Causes skin irritation. H332 Harmful if inhaled. H351 Suspected of causing cancer. H373 May cause damage to organs through prolonged or repeated exposure. H411 Toxic to aquatic life with long lasting effects.
--------------------------	--

## Neste Tempera Non-Road Diesel; Neste Pro Non-Road Diesel; MGODMA; DMA Barge

<b>Precautionary statements</b>	<p>P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.</p> <p>P273 Avoid release to the environment.</p> <p>P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.</p> <p>P302+P352 IF ON SKIN: Wash with plenty of water.</p> <p>P331 Do NOT induce vomiting.</p> <p>P261 Avoid breathing vapours.</p>
<b>Contains</b>	Fuels, diesel, Renewable hydrocarbons (diesel type fraction)

### 2.3. Other hazards

<b>Other hazards</b>	Evaporates slowly. Risk of soil and ground water contamination.
----------------------	---

## SECTION 3: Composition/information on ingredients

### 3.2. Mixtures

<b>Fuels, diesel</b>	<b>≥ 60 %</b>
CAS number: 68334-30-5	EC number: 269-822-7
	REACH registration number: 01-2119484664-27-XXXX
<b>Classification</b>	
Flam. Liq. 3 - H226	
Acute Tox. 4 - H332	
Skin Irrit. 2 - H315	
Carc. 2 - H351	
STOT RE 2 - H373	
Asp. Tox. 1 - H304	
Aquatic Chronic 2 - H411	
<b>Renewable hydrocarbons (diesel type fraction)</b>	<b>≤ 40 %</b>
CAS number: —	REACH registration number: 01-2119450077-42-XXXX
<b>Classification</b>	
Asp. Tox. 1 - H304	

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

<b>Composition comments</b>	Mixture of renewable raw material fuel, petroleum product and additives. Contains kerosine streams and straight-run and hydrocracked gas oil streams.
<b>Other information</b>	Renewable hydrocarbons (diesel type fraction);, Identity outside the EU (CAS number and name of the substance);, Alkanes, C10-20-branched and linear, CAS 928771-01-1.

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

<b>Inhalation</b>	Remove person to fresh air and keep comfortable for breathing. Get medical attention if symptoms are severe or persist.
<b>Ingestion</b>	Do not induce vomiting. Get medical attention immediately.
<b>Skin contact</b>	Remove contaminated clothing immediately and wash skin with soap and water. Get medical attention if irritation persists after washing.

## Neste Tempera Non-Road Diesel; Neste Pro Non-Road Diesel; MGODMA; DMA Barge

**Eye contact** Rinse immediately with plenty of water. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation persists after washing.

### 4.2. Most important symptoms and effects, both acute and delayed

**General information** Irritating to skin. May irritate eyes. Harmful by inhalation. Aspiration hazard if swallowed. Entry into the lungs following ingestion or vomiting may cause chemical pneumonitis.

### 4.3. Indication of any immediate medical attention and special treatment needed

**Notes for the doctor** Treat symptomatically.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

**Suitable extinguishing media** Water spray, foam, dry powder or carbon dioxide.

**Unsuitable extinguishing media** Do not use water jet as an extinguisher, as this will spread the fire.

### 5.2. Special hazards arising from the substance or mixture

**Specific hazards** Flammable liquid and vapour. Containers can burst violently or explode when heated, due to excessive pressure build-up.

**Hazardous combustion products** Carbon dioxide (CO<sub>2</sub>). Carbon monoxide (CO).

### 5.3. Advice for firefighters

**Protective actions during firefighting** Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk. Prevent fire extinguishing water from contaminating surface water or the ground water system.

**Special protective equipment for firefighters** Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

**Personal precautions** Avoid inhalation of vapours and contact with skin and eyes. Wear adequate protective equipment at all operations.

**For emergency responders** Prevent unauthorized access. Vapours are heavier than air and may spread near ground and travel a considerable distance to a source of ignition and flash back. Eliminate all ignition sources if safe to do so. Take precautionary measures against static discharge.

### 6.2. Environmental precautions

**Environmental precautions** Avoid release to the environment. Stop leak if safe to do so. Avoid the spillage or runoff entering drains, sewers or watercourses. Contain spillage with sand, earth or other suitable non-combustible material. Inform the relevant authorities if environmental pollution occurs (sewers, waterways, soil or air). Risk of soil and ground water contamination.

### 6.3. Methods and material for containment and cleaning up

**Methods for cleaning up** Immediately start clean-up of the liquid and contaminated soil. Small Spillages: Absorb spillage with sand or other inert absorbent. Pay attention to the fire and health hazards caused by the product.

### 6.4. Reference to other sections

**Reference to other sections** For personal protection, see Section 8.

## Neste Tempera Non-Road Diesel; Neste Pro Non-Road Diesel; MGODMA; DMA Barge

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

**Usage precautions** The product contains volatile substances which may spread in the atmosphere. Avoid heat, flames and other sources of ignition. Take precautionary measures against static discharges. All handling should only take place in well-ventilated areas. Avoid inhalation of vapours and contact with skin and eyes. Use personal protective equipment and/or local ventilation when needed. Do not eat, drink or smoke when using this product. Wash hands and any other contaminated areas of the body with soap and water before leaving the work site. During tank operations follow special instructions (risk of oxygen displacement and hydrocarbons).

#### 7.2. Conditions for safe storage, including any incompatibilities

**Storage precautions** Flammable liquid storage. Store in accordance with local regulations. Store in a demarcated bunded area to prevent release to drains and/or watercourses. Take precautions against leakage by constructing collecting pools and sewerage systems as well as by surfacing the loading and unloading stations. Only store in correctly labelled containers. Use containers made of the following materials: Carbon steel. Stainless steel.

#### 7.3. Specific end use(s)

**Specific end use(s)** Not known.

### SECTION 8: Exposure controls/Personal protection

#### 8.1. Control parameters

##### Occupational exposure limits

-

**Ingredient comments** The individual limit values can be applied for the hydrocarbons. Diesel fuel as total hydrocarbons; ACGIH TLV®-TWA (8h) 100 mg/m<sup>3</sup> (IFV).

**PNEC** Not available.

#### Fuels, diesel (CAS: 68334-30-5)

**DNEL** Workers - Inhalation; Short term systemic effects: 4300 mg/m<sup>3</sup>, (15 min), Aerosol  
 Workers - Inhalation; Long term systemic effects: 68 mg/m<sup>3</sup>, (8h), Aerosol  
 Workers - Dermal; Long term systemic effects: 2,9 mg/kg/day, (8h)  
 Consumer - Inhalation; Short term systemic effects: 2600 mg/m<sup>3</sup>, (15 min), Aerosol  
 Consumer - Inhalation; Long term systemic effects: 20 mg/m<sup>3</sup>, (24h), Aerosol  
 Consumer - Dermal; Long term systemic effects: 1,3 mg/kg/day, (24h)

#### Renewable hydrocarbons (diesel type fraction)

**DNEL** Workers - Inhalation; Long term systemic effects: 147 mg/m<sup>3</sup>  
 Workers - Dermal; Long term systemic effects: 42 mg/kg/day  
 Consumer - Inhalation; Long term systemic effects: 94 mg/m<sup>3</sup>  
 Consumer - Dermal; Long term systemic effects: 18 mg/kg/day

#### 8.2. Exposure controls

**Appropriate engineering controls** All handling should only take place in well-ventilated areas. Use personal protective equipment and/or local ventilation when needed. Handle in accordance with good industrial hygiene and safety practice. During tank operations follow special instructions (risk of oxygen displacement and hydrocarbons).

**Eye/face protection** Tight-fitting safety glasses. Face shield when needed.

## Neste Tempera Non-Road Diesel; Neste Pro Non-Road Diesel; MGODMA; DMA Barge

<b>Hand protection</b>	Wear protective gloves. It is recommended that gloves are made of the following material: Nitrile rubber. Neoprene. Polyvinyl chloride (PVC). The selected gloves should have a breakthrough time of at least 8 hours. Protection class 6. Protective gloves according to standards EN 420 and EN 374. Change protective gloves regularly.
<b>Other skin and body protection</b>	Wear suitable protective clothing as protection against splashing or contamination. Wear anti-static protective clothing if there is a risk of ignition from static electricity.
<b>Respiratory protection</b>	Filter device/half mask Combination filter, type A2/P3. Filter device could be used maximum 2 hours at a time. Filter devices must not be used in conditions where the oxygen level is low (< 19 vol.-%). At high concentrations a breathing apparatus must be used (self-contained or fresh air hose breathing apparatus). Filter must be changed often enough. Respirator according to standard EN 140.
<b>Environmental exposure controls</b>	Take precautions against leakage by constructing collecting pools and sewerage systems as well as by surfacing the loading and unloading stations.

### SECTION 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

<b>Appearance</b>	Liquid.
<b>Colour</b>	Red.
<b>Odour</b>	Hydrocarbons. Mild.
<b>Odour threshold</b>	-
<b>pH</b>	-
<b>Melting point</b>	Cloud point $\leq 0^{\circ}\text{C}$
<b>Initial boiling point and range</b>	150...370°C (EN ISO 3405)
<b>Flash point</b>	> 55°C (EN ISO 2719)
<b>Upper/lower flammability or explosive limits</b>	Lower flammable/explosive limit: 1 % Estimated value. Upper flammable/explosive limit: 6 % Estimated value.
<b>Vapour pressure</b>	< 1 kPa @ 40°C
<b>Vapour density</b>	-
<b>Relative density</b>	0,80...0,85 @ 15/4°C (EN ISO 12185)
<b>Solubility(ies)</b>	The product has poor water-solubility. < 50 mg/l @ 20°C
<b>Partition coefficient</b>	log Kow: > 3
<b>Auto-ignition temperature</b>	~ 240°C Estimated value.
<b>Decomposition Temperature</b>	-
<b>Viscosity</b>	Kinematic viscosity $\leq 4,5 \text{ mm}^2/\text{s}$ @ 40°C
<b>Explosive properties</b>	Not considered to be explosive.
<b>Oxidising properties</b>	Does not meet the criteria for classification as oxidising.

#### 9.2. Other information

<b>Other information</b>	Not known.
--------------------------	------------

### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

## Neste Tempera Non-Road Diesel; Neste Pro Non-Road Diesel; MGODMA; DMA Barge

**Reactivity** There are no known reactivity hazards associated with this product.

### 10.2. Chemical stability

**Stability** Stable at normal ambient temperatures.

### 10.3. Possibility of hazardous reactions

**Possibility of hazardous reactions** No potentially hazardous reactions known.

### 10.4. Conditions to avoid

**Conditions to avoid** Keep away from heat, sparks and open flame.

### 10.5. Incompatible materials

**Materials to avoid** Oxidising agents.

### 10.6. Hazardous decomposition products

**Hazardous decomposition products** Does not decompose when used and stored as recommended.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

**Toxicological effects** Harmful if inhaled.

#### Acute toxicity - inhalation

**ATE inhalation (vapours mg/l)** 18.33

#### Skin corrosion/irritation

**Skin corrosion/irritation** Fuels, diesel: Irritating to skin. (OECD 404) Renewable hydrocarbons (diesel type fraction): Not classified. (EC B4) The product irritates mucous membranes and may cause abdominal discomfort if swallowed. May cause respiratory irritation.

#### Serious eye damage/irritation

**Serious eye damage/irritation** Based on available data the classification criteria are not met. (OECD 405, EC B5)

#### Skin sensitisation

**Skin sensitisation** Based on available data the classification criteria are not met. (OECD 406, EC B6)

#### Germ cell mutagenicity

**Genotoxicity - in vitro** Based on available data the classification criteria are not met. (OECD 471, EC B10, B13/14, B17)

#### Genotoxicity - in vivo

Based on available data the classification criteria are not met. Fuels, diesel: (OECD 475)

#### Carcinogenicity

**Carcinogenicity** Suspected of causing cancer. Fuels, diesel: Product may contain cracked gas oil streams. Contains a substance/a group of substances which may cause cancer.

#### Reproductive toxicity

**Reproductive toxicity - fertility** Based on available data the classification criteria are not met. Renewable hydrocarbons (diesel type fraction): (OECD 416)

#### Reproductive toxicity - development

Based on available data the classification criteria are not met. Fuels, diesel: (OECD 414)

#### Specific target organ toxicity - single exposure

**STOT - single exposure** Not classified as a specific target organ toxicant after a single exposure.

## Neste Tempera Non-Road Diesel; Neste Pro Non-Road Diesel; MGODMA; DMA Barge

### Specific target organ toxicity - repeated exposure

**STOT - repeated exposure** Fuels, diesel: May cause damage to organs through prolonged or repeated exposure. (OECD 410, 411, 413) Renewable hydrocarbons (diesel type fraction): Not classified. (OECD 408)

### Aspiration hazard

**Aspiration hazard** May be fatal if swallowed and enters airways. Entry into the lungs following ingestion or vomiting may cause chemical pneumonitis.

### Toxicological information on ingredients.

#### Fuels, diesel

##### Acute toxicity - oral

**Notes (oral LD<sub>50</sub>)** LD<sub>50</sub> > 5000 mg/kg, Oral, Rat (OECD 401, 420)

##### Acute toxicity - dermal

**Notes (dermal LD<sub>50</sub>)** LD<sub>50</sub> > 4300 mg/kg, Dermal, Rabbit (OECD 434)

##### Acute toxicity - inhalation

**Notes (inhalation LC<sub>50</sub>)** LC<sub>50</sub> 3,6 - 5,4 mg/l, Inhalation, (4h), Rat (OECD 403)

**ATE inhalation (vapours mg/l)** 11.0

#### Renewable hydrocarbons (diesel type fraction)

##### Acute toxicity - oral

**Notes (oral LD<sub>50</sub>)** LD<sub>50</sub> >2000 mg/kg, Oral, Rat (EC B1 tris)

##### Acute toxicity - dermal

**Notes (dermal LD<sub>50</sub>)** LD<sub>50</sub> > 2000 mg/kg, Dermal, Rat (EC B3)

## SECTION 12: Ecological information

### 12.1. Toxicity

**Toxicity** Toxic to aquatic life with long lasting effects.

### Ecological information on ingredients.

#### Fuels, diesel

##### Acute aquatic toxicity

**Acute toxicity - fish** LL<sub>50</sub>, 96 hours: 21 mg/l, Oncorhynchus mykiss (Rainbow trout)  
NOEL, 96 hours: 10 mg/l, Oncorhynchus mykiss (Rainbow trout)  
WAF (OECD 203, EC C.1)

**Acute toxicity - aquatic invertebrates** EL50, 48 hours: 68 mg/l, Daphnia magna  
NOEL, 48 hours: 46 mg/l, Daphnia magna  
WAF (OECD 202, EC C.2)

**Acute toxicity - aquatic plants** EbL50, 72 hours: 10 mg/l, Pseudokirchneriella subcapitata  
NOEL, 72 hours: 1 mg/l, Pseudokirchneriella subcapitata  
WAF (OECD 201, EC C.3)

**Acute toxicity - microorganisms** EL50, 40 hours: > 1000 mg/l, Micro-organisms (wastewater sludge)  
NOEL, 40 hours: 3,22 mg/l, Micro-organisms (wastewater sludge)  
(QSAR)

##### Chronic aquatic toxicity

## Neste Tempera Non-Road Diesel; Neste Pro Non-Road Diesel; MGODMA; DMA Barge

**Chronic toxicity - fish early life stage** NOEL, 14 days: 0,08 mg/l, Oncorhynchus mykiss (Rainbow trout) (QSAR)

**Chronic toxicity - aquatic invertebrates** NOEL, 21 days: 0,2 mg/l, Daphnia magna (QSAR)

### Renewable hydrocarbons (diesel type fraction)

#### Acute aquatic toxicity

**Acute toxicity - fish** LL<sub>50</sub>, 96 hours: > 1000 mg/l, WAF (OECD 203)

**Acute toxicity - aquatic invertebrates** EL<sub>50</sub>, 48 hours: > 100 mg/l, WAF (OECD 202)

**Acute toxicity - aquatic plants** EL<sub>50</sub>, 72 hours: > 100 mg/l, Algae WAF (OECD 201)

**Acute toxicity - microorganisms** EC<sub>50</sub>, 30-180 minutes: > 1000 mg/l, Micro-organisms (wastewater sludge) (OECD 209)

#### Chronic aquatic toxicity

**Chronic toxicity - aquatic invertebrates** NOEC, 21 days: 1 mg/l, LOEC, 21 days: 3,2 mg/l, WAF (OECD 211)  
Sediment organisms  
NOEC, 10 days: 373 mg/kg, LOEC, 10 days: 1165 mg/kg, LC<sub>50</sub>, 10 days: 1200 mg/kg, (OSPAR Protocols, Part A: Sediment Bioassay, 2005)

### 12.2. Persistence and degradability

**Persistence and degradability** The product contains volatile substances which may spread in the atmosphere. Can be photodegraded in the atmosphere.

**Stability (hydrolysis)** No significant reaction in water.

### Ecological information on ingredients.

#### Fuels, diesel

**Biodegradation** Inherently biodegradable. (OECD 301F)

### Renewable hydrocarbons (diesel type fraction)

**Biodegradation** Rapidly degradable (OECD 301B)

### 12.3. Bioaccumulative potential

**Bioaccumulative potential** Possibly bioaccumulative.

**Partition coefficient** log K<sub>ow</sub>: > 3

### 12.4. Mobility in soil

**Mobility** Evaporates slowly. The product has poor water-solubility. Product can penetrate soil until reaching the surface of ground water. The product contains substances which are bound to particulate matter and are retained in soil.



## Neste Tempera Non-Road Diesel; Neste Pro Non-Road Diesel; MGODMA; DMA Barge

### 12.5. Results of PBT and vPvB assessment

**Results of PBT and vPvB assessment** This product does not contain any substances classified as PBT or vPvB.

### 12.6. Other adverse effects

**Other adverse effects** Product causes fouling, and direct contact produces harmful effects e.g. to birds and vegetation. Adsorbed hydrocarbon residues can be harmful to sediment organisms.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

**Disposal methods** Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority. When handling waste, the safety precautions applying to handling of the product should be considered. Care should be taken when handling emptied containers that have not been thoroughly cleaned or rinsed out.

## SECTION 14: Transport information

**Sea transport notes** This cargo is considered an Energy-rich fuel and effective 1 January 2019 should be carried subject to Annex I of MARPOL, see Annex 12 of MEPC.2/Circ.24. Please also refer to MEPC.1/Circ.879 - GUIDELINES FOR THE CARRIAGE OF ENERGY-RICH FUELS AND THEIR BLENDS

### 14.1. UN number

**UN No. (ADR/RID)** 1202

### 14.2. UN proper shipping name

**Proper shipping name (ADR/RID)** UN 1202 HEATING OIL, LIGHT

### 14.3. Transport hazard class(es)

**ADR/RID class** 3

### 14.4. Packing group

**ADR/RID packing group** III

### 14.5. Environmental hazards

**Environmentally hazardous substance/marine pollutant**  
MARINE POLLUTANT

### 14.6. Special precautions for user

**Tunnel restriction code** (D/E)

### 14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code** Bulk (MARPOL 73/78, Annex I): Energy-rich fuels

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

## Neste Tempera Non-Road Diesel; Neste Pro Non-Road Diesel; MGODMA; DMA Barge

<b>EU legislation</b>	Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended). Commission Regulation (EU) No 2015/830 of 28 May 2015. Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).
-----------------------	--

### 15.2. Chemical safety assessment

A chemical safety assessment has been carried out.

### SECTION 16: Other information

<b>Abbreviations and acronyms used in the safety data sheet</b>	ATE = Acute Toxicity Estimate DNEL = Derived No-Effect Level PNEC = Predicted No-Effect Concentration WAF = Water Accommodated Fraction
<b>Key literature references and sources for data</b>	Regulations, databases, literature, own research. Concawe Report No 6/05, 01/54, 11/10, 10/14. Chemical Safety Report Fuels, diesel, 2017. Chemical Safety Report Renewable hydrocarbons (diesel type fraction), 2016.
<b>Training advice</b>	DO NOT SIPHON PRODUCT BY MOUTH SUCTION.
<b>Revision comments</b>	Updated, sections: 14 NOTE: Lines within the margin indicate significant changes from the previous revision.
<b>Revision date</b>	01/01/2019
<b>Supersedes date</b>	03/09/2018
<b>SDS number</b>	5676
<b>Hazard statements in full</b>	H226 Flammable liquid and vapour. H304 May be fatal if swallowed and enters airways. H315 Causes skin irritation. H332 Harmful if inhaled. H351 Suspected of causing cancer. H373 May cause damage to organs through prolonged or repeated exposure. H411 Toxic to aquatic life with long lasting effects.
<b>Use Descriptor Codes, Industrial uses</b>	Distribution of substance,, (SU 3; PROC: 1, 2, 3, 4, 8a, 8b, 9, 15; ERC: 4, 5, 6a, 6b, 6c, 6d, 7), Use as a fuel,, (SU 3; PROC: 1, 2, 3, 8a, 8b, 16; ERC: 7)
<b>Use Descriptor Codes, Professional uses</b>	Use as a fuel,, (SU 22; PROC: 1, 2, 3, 8a, 8b, 16; ERC: 9a, 9b)
<b>Use Descriptor Codes, Consumer uses</b>	Use as a fuel,, (SU 21; PC 13; ERC: 9a, 9b)

## Exposure scenario

### Distribution of Substance

#### Identification

<b>Product name</b>	Fuels, diesel
<b>CAS number</b>	68334-30-5
<b>Version number</b>	2018
<b>Es reference</b>	ES01a

#### 1. Title of exposure scenario

<b>Main title</b>	Distribution of Substance
<b>Process scope</b>	Loading (including marine vessel/barge, rail/road car and IBC loading) and repacking (including drums and small packs) of substance, including its sampling, storage, unloading distribution and associated laboratory activities.

#### Environment

<b>Environmental release category</b>	ERC4 Use of non-reactive processing aid at industrial site (no inclusion into or onto article) ERC5 Use at industrial site leading to inclusion into/onto article ERC6a Use of intermediate ERC6b Use of reactive processing aid at industrial site (no inclusion into or onto article) ERC6c Use of monomer in polymerisation processes at industrial site (inclusion or not into/onto article) ERC6d Use of reactive process regulators in polymerisation processes at industrial site (inclusion or not into/onto article) ERC7 Use of functional fluid at industrial site
---------------------------------------	---

<b>SPERC</b>	ESVOC SPERC 1.1b.v1
--------------	---------------------

#### Worker

<b>Process category</b>	PROC1 Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions PROC2 Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions PROC3 Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition PROC4 Chemical production where opportunity for exposure arises PROC8a Transfer of substance or mixture (charging and discharging) at non-dedicated facilities PROC8b Transfer of substance or mixture (charging and discharging) at dedicated facilities PROC9 Transfer of substance or mixture into small containers (dedicated filling line, including weighing) PROC15 Use as laboratory reagent.
-------------------------	---

#### 2. Conditions of use affecting exposure (Industrial - Environment 1)

#### Product characteristics

Substance is complex UVCB. Predominantly hydrophobic.

#### Amounts used

## Distribution of Substance

Fraction of EU tonnage used in region: 0.1  
 Regional use tonnage: 31 000 000 tonnes/year  
 Fraction of Regional tonnage used locally: 0.002  
 Annual site tonnage: 61 000 tonnes  
 Maximum daily site tonnage: 200 tonne/day

### Frequency and duration of use

Continuous release.  
 Emission days: 300 days/year

### Other given operational conditions affecting environmental exposure

**Emission factor - air** Release fraction to air from process (initial release prior to RMM): 0.001  
**Emission factor - water** Release fraction to wastewater from process (initial release prior to RMM): 0.00001  
**Emission factor - soil** Release fraction to soil from process (initial release prior to RMM): 0.00001

### Environmental factors not influenced by risk management measures

**Dilution** Local freshwater dilution factor: 10  
 Local marine water dilution factor: 100

### Risk management measures

**Good practice** Common practices vary across sites, thus conservative process release estimates used.  
 Risk from environmental exposure is driven by freshwater sediment.

**STP details** Estimated substance removal from wastewater via domestic sewage treatment: 94.9%  
 Removal efficiency (total): 94.9%  
 Maximum allowable site tonnage (Msafe), based on release following total wastewater treatment removal: 1000 tonne/day  
 2000.  
 Assumed domestic sewage treatment plant flow (m<sup>3</sup>/day):

### Technical onsite conditions and measures to reduce or limit discharges to air, water and soil

**Air** Treat air emission to provide a typical removal efficiency of 90%.  
**Water** Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of (%): 74.3. If discharging to domestic sewage treatment plant, no onsite wastewater treatment required.  
**Soil** Do not apply industrial sludge to natural soils. Sludge should be incinerated, contained or reclaimed.

### Conditions and measures related to external treatment of waste for disposal

**Waste treatment** External treatment and disposal of waste should comply with applicable local and/or national regulations.

### Conditions and measures related to external recovery of waste

**Recovery method** External recovery and recycling of waste should comply with applicable local and/or national regulations.

## 2. Conditions of use affecting exposure (Workers - Health 1)

### Product characteristics

**Physical state** Liquid With potential for aerosol generation  
**Vapour pressure** Vapour pressure < 0.5 kPa at STP.  
**Concentration details** Covers percentage substance in the product up to 100% (unless stated differently).

## Distribution of Substance

### Frequency and duration of use

Covers daily exposures up to 8 hours (unless stated differently).

### Other given operational conditions affecting workers exposure

**Setting** Assumes a good basic standard of occupational hygiene is implemented.

**Temperature** Assumes use at not more than 20°C above ambient temperature, unless stated differently.

### Organisational measures to prevent/limit releases, dispersion and exposure

**Organisational measures** General measures applicable to all activities Control any potential exposure using measures such as contained or enclosed systems, properly designed and maintained facilities and a good standard of general ventilation. Drain down systems and clear transfer lines prior to breaking containment. Drain down and flush equipment where possible prior to maintenance. Where there is potential for exposure: Ensure relevant staff are informed of the nature of exposure and aware of basic actions to minimise exposures; Ensure suitable personal protective equipment is available; Clear up spills and dispose of waste in accordance with regulatory requirements; monitor effectiveness of control measures; consider the need for health surveillance; identify and implement corrective actions. . General measures (skin irritants) Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent/minimise exposures and to report any skin problems that may develop.

### Risk management measures

General exposures (closed systems)  
Handle substance within a closed system.

General exposures (open systems)  
Wear suitable gloves tested to EN374.

Process sampling  
No other specific measures identified.

Laboratory activities  
No other specific measures identified.

Bulk closed loading and unloading  
Handle substance within a closed system.  
Wear suitable gloves tested to EN374.

Bulk open loading and unloading  
Wear suitable gloves tested to EN374.

Drum and small package filling  
Wear suitable gloves tested to EN374.

Equipment cleaning and maintenance  
Drain down and flush system prior to equipment break-in or maintenance.  
Wear chemically-resistant gloves (tested to EN374) in combination with 'basic' employee training.

Storage  
Handle substance within a closed system.

## Distribution of Substance

### 3. Exposure estimation (Environment 1)

<b>Assessment method</b>	Used Petrorisk model. (Hydrocarbon Block Method)  Risk-driving RCR - air compartment driven $RCR(\text{air}) \leq 0.024$ Risk-driving RCR - water compartment driven $RCR(\text{water}) \leq 0.20$
--------------------------	--

### 4. Guidance to check compliance with the exposure scenario (Environment 1)

Guidance is based on assumed operating conditions which may not be applicable to all sites, thus, scaling may be necessary to define appropriate site-specific risk management measures. Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination. Required removal efficiency for air can be achieved using onsite technologies, either alone or in combination. Further details on scaling and control technologies are provided in SpERC factsheet (<http://cefic.org/en/reach-for-industries-libraries.html>).

### 3. Exposure estimation (Health 1)

<b>Assessment method</b>	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated  Available hazard data do not enable the derivation of a DNEL for dermal irritant effects. Available hazard data do not support the need for a DNEL to be established for other health effects. Qualitative approach used to conclude safe use.
--------------------------	--

### 4. Guidance to check compliance with the exposure scenario (Health 1)

Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented. Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

## Exposure scenario

### Use as a Fuel - Industrial

#### Identification

Product name	Fuels, diesel
CAS number	68334-30-5
Version number	2018
Es reference	ES12a

#### 1. Title of exposure scenario

<b>Main title</b>	Use as a Fuel - Industrial
<b>Process scope</b>	Covers the use as a fuel (or fuel additive) and includes activities associated with its transfer, use, equipment maintenance and handling of waste.
<b>Environment</b>	
<b>Environmental release category</b>	ERC7 Use of functional fluid at industrial site
<b>SPERC</b>	ESVOC SPERC 7.12a.v1
<b>Worker</b>	
<b>Process category</b>	<p>PROC1 Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions</p> <p>PROC2 Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions</p> <p>PROC3 Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition</p> <p>PROC8a Transfer of substance or mixture (charging and discharging) at non-dedicated facilities</p> <p>PROC8b Transfer of substance or mixture (charging and discharging) at dedicated facilities</p> <p>PROC16 Use of fuels</p>

#### 2. Conditions of use affecting exposure (Industrial - Environment 1)

##### Product characteristics

Substance is complex UVCB. Predominantly hydrophobic.

##### Amounts used

Fraction of EU tonnage used in region: 0.1  
 Regional use tonnage: 3 700 000 tonnes/year  
 Fraction of Regional tonnage used locally: 0.4  
 Annual site tonnage: 1 500 000 tonnes  
 Maximum daily site tonnage: 5,000 tonne/day

##### Frequency and duration of use

Continuous release.  
 Emission days: 300 days/year

##### Other given operational conditions affecting environmental exposure

<b>Emission factor - air</b>	Release fraction to air from process (initial release prior to RMM): 0.005
<b>Emission factor - water</b>	Release fraction to wastewater from process (initial release prior to RMM): 2.4E-06

## Use as a Fuel - Industrial

**Emission factor - soil** Release fraction to soil from process (initial release prior to RMM): 0

### Environmental factors not influenced by risk management measures

**Dilution** Local freshwater dilution factor: 10  
Local marine water dilution factor: 100

### Risk management measures

**Good practice** Common practices vary across sites, thus conservative process release estimates used.  
Risk from environmental exposure is driven by freshwater sediment.

**STP details** Estimated substance removal from wastewater via domestic sewage treatment: 94.9%  
Removal efficiency (total): 98.7%  
Maximum allowable site tonnage (M<sub>safe</sub>), based on release following total wastewater treatment removal: 5 000 tonne/day  
Assumed domestic sewage treatment plant flow (m<sup>3</sup>/day): 2000.

### Technical onsite conditions and measures to reduce or limit discharges to air, water and soil

**Air** Treat air emission to provide a typical removal efficiency of 95%.

**Water** Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of (%): ≥ 94.4. If discharging to domestic sewage treatment plant, provide the required onsite wastewater removal efficiency of (%): ≥ 0.

**Soil** Do not apply industrial sludge to natural soils. Sludge should be incinerated, contained or reclaimed.

### Conditions and measures related to external treatment of waste for disposal

**Waste treatment** Combustion emissions limited by required exhaust emission controls. Combustion emissions considered in regional exposure assessment. External treatment and disposal of waste should comply with applicable local and/or national regulations.

### Conditions and measures related to external recovery of waste

**Recovery method** This substance is consumed during use and no waste of the substance is generated.

## 2. Conditions of use affecting exposure (Workers - Health 1)

### Product characteristics

**Physical state** Liquid With potential for aerosol generation

**Vapour pressure** Vapour pressure < 0.5 kPa at STP.

**Concentration details** Covers percentage substance in the product up to 100% (unless stated differently).

### Frequency and duration of use

Covers daily exposures up to 8 hours (unless stated differently).

### Other given operational conditions affecting workers exposure

**Setting** Assumes a good basic standard of occupational hygiene is implemented.

**Temperature** Assumes use at not more than 20°C above ambient temperature, unless stated differently.

### Organisational measures to prevent/limit releases, dispersion and exposure



## Use as a Fuel - Industrial

### Organisational measures

General measures applicable to all activities Control any potential exposure using measures such as contained or enclosed systems, properly designed and maintained facilities and a good standard of general ventilation. Drain down systems and clear transfer lines prior to breaking containment. Drain down and flush equipment where possible prior to maintenance. Where there is potential for exposure: Ensure relevant staff are informed of the nature of exposure and aware of basic actions to minimise exposures; Ensure suitable personal protective equipment is available; Clear up spills and dispose of waste in accordance with regulatory requirements; monitor effectiveness of control measures; consider the need for health surveillance; identify and implement corrective actions. . General measures (skin irritants) Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent/minimise exposures and to report any skin problems that may develop.

### Risk management measures

#### Bulk transfers

Wear suitable gloves tested to EN374.

.

#### Drum/batch transfers

Wear suitable gloves tested to EN374.

.

#### Use as a fuel

(closed systems)

No other specific measures identified.

.

#### Equipment cleaning and maintenance

Drain down and flush system prior to equipment break-in or maintenance.

Wear chemically-resistant gloves (tested to EN374) in combination with 'basic' employee training.

.

#### Storage

Handle substance within a closed system.

### 3. Exposure estimation (Environment 1)

#### Assessment method

Used Petrorisk model. (Hydrocarbon Block Method)

Risk-driving RCR - air compartment driven  $RCR(\text{air}) \leq 0.028$  Risk-driving RCR - water compartment driven  $RCR(\text{water}) \leq 0.91$

### 4. Guidance to check compliance with the exposure scenario (Environment 1)

Guidance is based on assumed operating conditions which may not be applicable to all sites, thus, scaling may be necessary to define appropriate site-specific risk management measures. Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination. Required removal efficiency for air can be achieved using onsite technologies, either alone or in combination. Further details on scaling and control technologies are provided in SpERC factsheet (<http://cefic.org/en/reach-for-industries-libraries.html>).

### 3. Exposure estimation (Health 1)

#### Assessment method

The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated

## Use as a Fuel - Industrial

Available hazard data do not enable the derivation of a DNEL for dermal irritant effects.  
Available hazard data do not support the need for a DNEL to be established for other health effects. Qualitative approach used to conclude safe use.

### 4. Guidance to check compliance with the exposure scenario (Health 1)

Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented. Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

## Exposure scenario

### Use as a Fuel - Professional

#### Identification

<b>Product name</b>	Fuels, diesel
<b>CAS number</b>	68334-30-5
<b>Version number</b>	2018
<b>Es reference</b>	ES12b

#### 1. Title of exposure scenario

<b>Main title</b>	Use as a Fuel - Professional
<b>Process scope</b>	Covers the use as a fuel (or fuel additive) and includes activities associated with its transfer, use, equipment maintenance and handling of waste.

#### Environment

<b>Environmental release category</b>	ERC9a Widespread use of functional fluid (indoor) ERC9b Widespread use of functional fluid (outdoor)
---------------------------------------	---

<b>SPERC</b>	ESVOC SPERC 9.12b.v1
--------------	----------------------

#### Worker

<b>Process category</b>	PROC1 Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions PROC2 Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions PROC3 Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition PROC8a Transfer of substance or mixture (charging and discharging) at non-dedicated facilities PROC8b Transfer of substance or mixture (charging and discharging) at dedicated facilities PROC16 Use of fuels
-------------------------	---

#### 2. Conditions of use affecting exposure (Industrial - Environment 1)

#### Product characteristics

Substance is complex UVCB. Predominantly hydrophobic.

#### Amounts used

Fraction of EU tonnage used in region: 0.1  
Regional use tonnage: 6 900 000 tonnes/year  
Fraction of Regional tonnage used locally: 0.0005  
Annual site tonnage: 3 400 tonnes  
Maximum daily site tonnage: 9.4 tonne/day

#### Frequency and duration of use

Continuous release.  
Emission days: 365 days/year

#### Other given operational conditions affecting environmental exposure

<b>Emission factor - air</b>	Release fraction to air from wide dispersive use (regional only): 0.001
<b>Emission factor - water</b>	Release fraction to wastewater from wide dispersive use: 0.00001

## Use as a Fuel - Professional

**Emission factor - soil** Release fraction to soil from wide dispersive use (regional only): 0.00001

### Environmental factors not influenced by risk management measures

**Dilution** Local freshwater dilution factor: 10  
Local marine water dilution factor: 100

### Risk management measures

**Good practice** Common practices vary across sites, thus conservative process release estimates used.  
Risk from environmental exposure is driven by fresh water.

**STP details** Estimated substance removal from wastewater via domestic sewage treatment: 94.9%  
Removal efficiency (total): 94.9%  
Maximum allowable site tonnage (M<sub>safe</sub>), based on release following total wastewater treatment removal: 1.2E+05 kg/day  
Assumed domestic sewage treatment plant flow (m<sup>3</sup>/day): 2000.

### Technical onsite conditions and measures to reduce or limit discharges to air, water and soil

**Air** Not determined.

**Water** Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of (%): ≥ 34.3. If discharging to domestic sewage treatment plant, no onsite wastewater treatment required.

**Soil** Do not apply industrial sludge to natural soils. Sludge should be incinerated, contained or reclaimed.

### Conditions and measures related to external treatment of waste for disposal

**Waste treatment** Combustion emissions limited by required exhaust emission controls. Combustion emissions considered in regional exposure assessment. External treatment and disposal of waste should comply with applicable local and/or national regulations.

### Conditions and measures related to external recovery of waste

**Recovery method** This substance is consumed during use and no waste of the substance is generated.

## 2. Conditions of use affecting exposure (Workers - Health 1)

### Product characteristics

**Physical state** Liquid With potential for aerosol generation

**Vapour pressure** Vapour pressure < 0.5 kPa at STP.

**Concentration details** Covers percentage substance in the product up to 100% (unless stated differently).

### Frequency and duration of use

Covers daily exposures up to 8 hours (unless stated differently).

### Other given operational conditions affecting workers exposure

**Setting** Assumes a good basic standard of occupational hygiene is implemented.

**Temperature** Assumes use at not more than 20°C above ambient temperature, unless stated differently.

### Organisational measures to prevent/limit releases, dispersion and exposure

## Use as a Fuel - Professional

### Organisational measures

General measures applicable to all activities Control any potential exposure using measures such as contained or enclosed systems, properly designed and maintained facilities and a good standard of general ventilation. Drain down systems and clear transfer lines prior to breaking containment. Drain down and flush equipment where possible prior to maintenance. Where there is potential for exposure: Ensure relevant staff are informed of the nature of exposure and aware of basic actions to minimise exposures; Ensure suitable personal protective equipment is available; Clear up spills and dispose of waste in accordance with regulatory requirements; monitor effectiveness of control measures; consider the need for health surveillance; identify and implement corrective actions. . General measures (skin irritants) Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent/minimise exposures and to report any skin problems that may develop.

### Risk management measures

#### Bulk transfers

Wear suitable gloves tested to EN374.

.

#### Drum/batch transfers

Use drum pumps or carefully pour from container.

Wear suitable gloves tested to EN374.

.

#### Refuelling

Wear suitable gloves tested to EN374.

.

#### Use as a fuel

(closed systems)

Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour).

, or:

Ensure operation is undertaken outdoors.

.

#### Equipment cleaning and maintenance

Drain down and flush system prior to equipment break-in or maintenance.

Wear chemically-resistant gloves (tested to EN374) in combination with 'basic' employee training.

.

#### Storage

Handle substance within a closed system.

### 3. Exposure estimation (Environment 1)

#### Assessment method

Used Petrorisk model. (Hydrocarbon Block Method)

Risk-driving RCR - air compartment driven  $RCR(\text{air}) \leq 0.024$  Risk-driving RCR - water compartment driven  $RCR(\text{water}) \leq 0.075$

### 4. Guidance to check compliance with the exposure scenario (Environment 1)

Guidance is based on assumed operating conditions which may not be applicable to all sites, thus, scaling may be necessary to define appropriate site-specific risk management measures. Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination. Required removal efficiency for air can be achieved using onsite technologies, either alone or in combination. Further details on scaling and control technologies are provided in SpERC factsheet (<http://cefic.org/en/reach-for-industries-libraries.html>).

## Use as a Fuel - Professional

### 3. Exposure estimation (Health 1)

**Assessment method**

The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated

Available hazard data do not enable the derivation of a DNEL for dermal irritant effects. Available hazard data do not support the need for a DNEL to be established for other health effects. Qualitative approach used to conclude safe use.

### 4. Guidance to check compliance with the exposure scenario (Health 1)

Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented. Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

## Exposure scenario

### Use as a Fuel - Consumer

#### Identification

Product name	Fuels, diesel
CAS number	68334-30-5
Version number	2018
Es reference	ES12c

#### 1. Title of exposure scenario

Main title	Use as a Fuel - Consumer
Process scope	Covers consumer uses in liquid fuels.
Product category	PC13 Fuels.
<u>Environment</u>	
Environmental release category	ERC9a Widespread use of functional fluid (indoor) ERC9b Widespread use of functional fluid (outdoor)
SPERC	ESVOC SPERC 9.12c.v1
<u>Non-industrial</u>	
Product sub-category	PC13_1 Liquid: automotive refuelling PC13_3 Liquid: garden equipment - use PC13_4 Liquid: Garden equipment - Refuelling PC13_6 Liquid: home space heater fuel

#### 2. Conditions of use affecting exposure (Non-industrial - Environment 1)

##### Product characteristics

Substance is complex UVCB. Predominantly hydrophobic.

##### Amounts used

Fraction of EU tonnage used in region: 0.1  
Regional use tonnage: 19 000 000 tonnes/year  
Fraction of Regional tonnage used locally: 0.0005  
Annual site tonnage: 9 500 tonnes  
Maximum daily site tonnage: 26 tonne/day

##### Frequency and duration of use

Continuous release.  
Emission days: 365 days/year

##### Other given operational conditions affecting environmental exposure

Emission factor - air	Release fraction to air from wide dispersive use (regional only): 0.001
Emission factor - water	Release fraction to wastewater from wide dispersive use: 0.00001
Emission factor - soil	Release fraction to soil from wide dispersive use (regional only): 0.00001

##### Environmental factors not influenced by risk management measures

Dilution	Local freshwater dilution factor: 10 Local marine water dilution factor: 100
----------	---

## Use as a Fuel - Consumer

### Risk management measures

#### **STP details**

Estimated substance removal from wastewater via domestic sewage treatment: 94.9%  
 Maximum allowable site tonnage (M<sub>safe</sub>), based on release following total wastewater treatment removal: 3.0E+05 kg/day  
 Assumed domestic sewage treatment plant flow (m<sup>3</sup>/day):  
 2000.

### Conditions and measures related to external treatment of waste for disposal

#### **Waste treatment**

Combustion emissions limited by required exhaust emission controls. Combustion emissions considered in regional exposure assessment. External treatment and disposal of waste should comply with applicable local and/or national regulations.

### Conditions and measures related to external recovery of waste

#### **Recovery method**

This substance is consumed during use and no waste of the substance is generated.

## 2. Conditions of use affecting exposure (Non-industrial - Health 1)

### Control of Non-industrial exposure

PC13\_1 Liquid: automotive refuelling

### Product characteristics

#### **Physical state**

Liquid

#### **Vapour pressure**

Liquid, vapour pressure > 10 Pa (STP)

#### **Concentration details**

Covers percentage substance in the product up to 100% (unless stated differently).

### Amounts used

For each use event, covers use amounts up to 37.5 kg.

### Frequency and duration of use

Covers use up to 52 days/year.  
 Covers use up to 1 time(s)/day.  
 Covers exposure up to 0.05 hours per event.

### Human factors not influenced by risk management

#### **Potentially exposed body parts**

Covers skin contact area up to 210.00 cm<sup>2</sup>.

### Other given operational conditions affecting Non-industrial exposure

#### **Room size**

Covers outdoor use. Covers use in room size of 100 m<sup>3</sup>.

### Other given operational conditions affecting Non-industrial exposure

No specific risk management measure identified beyond those operational conditions stated.

## 2. Conditions of use affecting exposure (Non-industrial - Health 2)

### Control of Non-industrial exposure

PC13\_3 Liquid: garden equipment - use

### Product characteristics

#### **Physical state**

Liquid

#### **Vapour pressure**

Vapour pressure > 10 kPa at STP.

#### **Concentration details**

Covers percentage substance in the product up to 100% (unless stated differently).



## Use as a Fuel - Consumer

### Amounts used

For each use event, covers use amounts up to 750 g.

### Frequency and duration of use

Covers use up to 26 day(s)/year.  
Covers use up to 1 time(s)/day.  
Covers exposure up to 2 hours per event.

### Human factors not influenced by risk management

**Potentially exposed body parts** Covers skin contact area up to 420 cm<sup>2</sup>.

### Other given operational conditions affecting Non-industrial exposure

**Room size** Covers outdoor use. Covers use in room size of 100 m<sup>3</sup>.

### Other given operational conditions affecting Non-industrial exposure

No specific risk management measure identified beyond those operational conditions stated.

## 2. Conditions of use affecting exposure (Non-industrial - Health 3)

### Control of Non-industrial exposure

PC13\_4 Liquid: Garden equipment - Refuelling

### Product characteristics

**Physical state** Liquid  
**Vapour pressure** Vapour pressure > 10 kPa at STP.  
**Concentration details** Covers percentage substance in the product up to 100% (unless stated differently).

### Amounts used

For each use event, covers use amounts up to 750 g.

### Frequency and duration of use

Covers use up to 26 day(s)/year.  
Covers use up to 1 time(s)/day.  
Covers exposure up to 0.03 hours per event.

### Human factors not influenced by risk management

**Potentially exposed body parts** Covers skin contact area up to 420 cm<sup>2</sup>.

### Other given operational conditions affecting Non-industrial exposure

**Room size** Covers use in room size of 34 m<sup>3</sup>. Covers use in a one car garage (34 m<sup>3</sup>) under typical ventilation.

### Other given operational conditions affecting Non-industrial exposure

No specific risk management measure identified beyond those operational conditions stated.

## 2. Conditions of use affecting exposure (Non-industrial - Health 4)

### Control of Non-industrial exposure

PC13\_6 Liquid: home space heater fuel

### Product characteristics

**Physical state** Liquid

## Use as a Fuel - Consumer

<b>Vapour pressure</b>	Vapour pressure > 10 kPa at STP.
<b>Concentration details</b>	Covers percentage substance in the product up to 100% (unless stated differently).

### Amounts used

For each use event, covers use amounts up to 1.5 kg.

### Frequency and duration of use

Covers use up to 120 day(s)/year.  
Covers use up to 1 time(s)/day.  
Covers exposure up to 0.03hours

### Human factors not influenced by risk management

<b>Potentially exposed body parts</b>	Covers skin contact area up to 210 cm <sup>2</sup> .
---------------------------------------	--

### Other given operational conditions affecting Non-industrial exposure

<b>Room size</b>	Covers use in room size of 20 m <sup>3</sup> . Covers use under typical household ventilation.
------------------	--

### Other given operational conditions affecting Non-industrial exposure

No specific risk management measure identified beyond those operational conditions stated.

### 3. Exposure estimation (Environment 1)

<b>Assessment method</b>	Used Petrorisk model. (Hydrocarbon Block Method)  Risk-driving RCR - air compartment driven $RCR(\text{air}) \leq 0.024$ Risk-driving RCR - water compartment driven $RCR(\text{water}) \leq 0.085$
--------------------------	---

### 4. Guidance to check compliance with the exposure scenario (Environment 1)

Guidance is based on assumed operating conditions which may not be applicable to all sites, thus, scaling may be necessary to define appropriate site-specific risk management measures.

### 3. Exposure estimation (Health 1)

<b>Assessment method</b>	The ECETOC TRA tool has been used to estimate consumer exposures, unless otherwise indicated. (ECETOC Report 107; Chapter R15 of IR&CSA TGD)
--------------------------	--

### 4. Guidance to check compliance with the exposure scenario (Health 1)

Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented. Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.