



SAFETY DATA SHEET

Diesel fuel, sulphur free; Neste Pro Diesel; Neste Futura Diesel

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name Diesel fuel, sulphur free; Neste Pro Diesel; Neste Futura Diesel

Product number ID 13865

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Distribution of substance, (ES01a)
Use as an intermediate, (ES01b)
Use as a fuel, (ES12a, ES12b, ES12c)

1.3. Details of the supplier of the safety data sheet

Supplier Neste Oyj
Keilaranta 21, Espoo, P.O.B. 95, FIN-00095 NESTE, FINLAND
Tel. +358 10 45811
SDS@neste.com (chemical safety)

1.4. Emergency telephone number

National emergency telephone number +358-9-471 977, +358-9-4711, Poison Information Centre

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)


Physical hazards Flam. Liq. 3 - H226

Health hazards Acute Tox. 4 - H332 Skin Irrit. 2 - H315 Carc. 2 - H351 STOT RE 2 - H373 Asp. Tox. 1 - H304

Environmental hazards Aquatic Chronic 2 - H411

2.2. Label elements

Pictogram



Signal word

Danger

Hazard statements

H226 Flammable liquid and vapour.
H304 May be fatal if swallowed and enters airways.
H315 Causes skin irritation.
H332 Harmful if inhaled.
H351 Suspected of causing cancer.
H373 May cause damage to organs through prolonged or repeated exposure.
H411 Toxic to aquatic life with long lasting effects.

Diesel fuel, sulphur free; Neste Pro Diesel; Neste Futura Diesel

Precautionary statements	<p>P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.</p> <p>P273 Avoid release to the environment.</p> <p>P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.</p> <p>P302+P352 IF ON SKIN: Wash with plenty of water.</p> <p>P331 Do NOT induce vomiting.</p> <p>P261 Avoid breathing vapours.</p>
Contains	<p>Fuels, diesel, Renewable hydrocarbons (diesel type fraction), Distillates (Fischer-Tropsch), C8-26 - branched and linear, Petroleum diesel/gas oil fraction, co-processed with renewable hydrocarbons of plant or animal origin</p>

2.3. Other hazards

Other hazards Evaporates slowly. Risk of soil and ground water contamination.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Fuels, diesel	0 - 100 %
CAS number: 68334-30-5 EC number: 269-822-7 REACH registration number: 01-2119484664-27-XXXX	
Classification Flam. Liq. 3 - H226 Acute Tox. 4 - H332 Skin Irrit. 2 - H315 Carc. 2 - H351 STOT RE 2 - H373 Asp. Tox. 1 - H304 Aquatic Chronic 2 - H411	
Distillates (Fischer-Tropsch), C8-26 - branched and linear	0 - 100 %
CAS number: 848301-67-7 EC number: 481-740-5 REACH registration number: 01-0000020119-75-XXXX	
Classification Asp. Tox. 1 - H304	
Renewable hydrocarbons (diesel type fraction)	0 - 80 %
CAS number: — REACH registration number: 01-2119450077-42-XXXX	
Classification Asp. Tox. 1 - H304	

Diesel fuel, sulphur free; Neste Pro Diesel; Neste Futura Diesel

Petroleum diesel/gas oil fraction, co-processed with renewable hydrocarbons of plant or animal origin	0 - 5 %
CAS number: —	REACH registration number: 01-2120091562-55-0001
Classification Flam. Liq. 3 - H226 Acute Tox. 4 - H332 Skin Irrit. 2 - H315 Carc. 2 - H351 STOT RE 2 - H373 Asp. Tox. 1 - H304 Aquatic Chronic 2 - H411	

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

Composition comments	Mixture of renewable raw material fuel, petroleum product and additives. Contains kerosine streams and straight-run and hydrocracked gas oil streams.
Other information	Renewable hydrocarbons (diesel type fraction);, Identity outside the EU (CAS number and name of the substance);, Alkanes, C10-C20 -branched and linear, CAS 928771-01-1.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation	Remove person to fresh air and keep comfortable for breathing. Get medical attention if symptoms are severe or persist.
Ingestion	Do not induce vomiting. Get medical attention immediately.
Skin contact	Remove contaminated clothing immediately and wash skin with soap and water. Get medical attention if irritation persists after washing.
Eye contact	Rinse immediately with plenty of water. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation persists after washing.

4.2. Most important symptoms and effects, both acute and delayed

General information	Irritating to skin. May irritate eyes. Harmful by inhalation. Entry into the lungs following ingestion or vomiting may cause chemical pneumonitis.
----------------------------	--

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor	Treat symptomatically.
-----------------------------	------------------------

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	Water spray, foam, dry powder or carbon dioxide.
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Specific hazards	Flammable liquid and vapour. Containers can burst violently or explode when heated, due to excessive pressure build-up.
Hazardous combustion products	Carbon dioxide (CO ₂). Carbon monoxide (CO).

Diesel fuel, sulphur free; Neste Pro Diesel; Neste Futura Diesel

5.3. Advice for firefighters

Protective actions during firefighting	Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk. Prevent fire extinguishing water from contaminating surface water or the ground water system.
Special protective equipment for firefighters	Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions	Avoid inhalation of vapours and contact with skin and eyes. Wear adequate protective equipment at all operations.
For emergency responders	Prevent unauthorized access. Vapours are heavier than air and may spread near ground and travel a considerable distance to a source of ignition and flash back. Eliminate all ignition sources if safe to do so. Take precautionary measures against static discharge.

6.2. Environmental precautions

Environmental precautions	Avoid release to the environment. Stop leak if safe to do so. Avoid the spillage or runoff entering drains, sewers or watercourses. Contain spillage with sand, earth or other suitable non-combustible material. Inform the relevant authorities if environmental pollution occurs (sewers, waterways, soil or air). Risk of soil and ground water contamination.
----------------------------------	--

6.3. Methods and material for containment and cleaning up

Methods for cleaning up	Immediately start clean-up of the liquid and contaminated soil. Small Spillages: Absorb spillage with sand or other inert absorbent. Pay attention to the fire and health hazards caused by the product.
--------------------------------	--

6.4. Reference to other sections

Reference to other sections	For personal protection, see Section 8.
------------------------------------	---

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions	The product contains volatile substances which may spread in the atmosphere. Avoid heat, flames and other sources of ignition. Take precautionary measures against static discharges. All handling should only take place in well-ventilated areas. Avoid inhalation of vapours and contact with skin and eyes. Use personal protective equipment and/or local ventilation when needed. Do not eat, drink or smoke when using this product. Wash hands and any other contaminated areas of the body with soap and water before leaving the work site. During tank operations follow special instructions (risk of oxygen displacement and hydrocarbons).
--------------------------	--

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions	Flammable liquid storage. Store in accordance with local regulations. Store in a demarcated bunded area to prevent release to drains and/or watercourses. Take precautions against leakage by constructing collecting pools and sewerage systems as well as by surfacing the loading and unloading stations. Only store in correctly labelled containers. Use containers made of the following materials: Carbon steel. Stainless steel.
----------------------------	--

7.3. Specific end use(s)

Specific end use(s)	Not known.
----------------------------	------------

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

Diesel fuel, sulphur free; Neste Pro Diesel; Neste Futura Diesel

Ingredient comments	The individual limit values can be applied for the hydrocarbons. Diesel fuel as total hydrocarbons; ACGIH TLV®-TWA (8h) 100 mg/m ³ (IFV).
PNEC	Not available.

Fuels, diesel (CAS: 68334-30-5)

DNEL	Workers - Inhalation; Short term systemic effects: 4300 mg/m ³ , (15 min), Aerosol Workers - Inhalation; Long term systemic effects: 68 mg/m ³ , (8h), Aerosol Workers - Dermal; Long term systemic effects: 2,9 mg/kg/day, (8h) Consumer - Inhalation; Short term systemic effects: 2600 mg/m ³ , (15 min), Aerosol Consumer - Inhalation; Long term systemic effects: 20 mg/m ³ , (24h), Aerosol Consumer - Dermal; Long term systemic effects: 1,3 mg/kg/day, (24h)
-------------	---

Renewable hydrocarbons (diesel type fraction)

DNEL	Workers - Inhalation; Long term systemic effects: 147 mg/m ³ Workers - Dermal; Long term systemic effects: 42 mg/kg/day Consumer - Inhalation; Long term systemic effects: 94 mg/m ³ Consumer - Dermal; Long term systemic effects: 18 mg/kg/day
-------------	---

8.2. Exposure controls

Appropriate engineering controls	All handling should only take place in well-ventilated areas. Use personal protective equipment and/or local ventilation when needed. Handle in accordance with good industrial hygiene and safety practice. During tank operations follow special instructions (risk of oxygen displacement and hydrocarbons).
Eye/face protection	Tight-fitting safety glasses. Face shield when needed.
Hand protection	Wear protective gloves. It is recommended that gloves are made of the following material: Nitrile rubber. Neoprene. Polyvinyl chloride (PVC). The selected gloves should have a breakthrough time of at least 8 hours. Protection class 6. Protective gloves according to standards EN 420 and EN 374. Change protective gloves regularly.
Other skin and body protection	Wear suitable protective clothing as protection against splashing or contamination. Wear anti-static protective clothing if there is a risk of ignition from static electricity.
Respiratory protection	Filter device/half mask Combination filter, type A2/P3. Filter device could be used maximum 2 hours at a time. Filter devices must not be used in conditions where the oxygen level is low (< 19 vol.-%). At high concentrations a breathing apparatus must be used (self-contained or fresh air hose breathing apparatus). Filter must be changed often enough. Respirator according to standard EN 140.
Environmental exposure controls	Take precautions against leakage by constructing collecting pools and sewerage systems as well as by surfacing the loading and unloading stations.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Appearance	Liquid.
Colour	Clear. Yellowish.
Odour	Hydrocarbons. Mild.
Odour threshold	-
pH	-
Melting point	Cloud point ≤ 0°C

Diesel fuel, sulphur free; Neste Pro Diesel; Neste Futura Diesel

Initial boiling point and range	150...370°C (EN ISO 3405)
Flash point	≥ 55°C (EN ISO 2719)
Upper/lower flammability or explosive limits	Upper flammable/explosive limit: 1 % Estimated value. Lower flammable/explosive limit: 6 % Estimated value.
Vapour pressure	< 1 kPa @ 40°C
Vapour density	-
Relative density	~ 0,8...0,85 @ 15/4°C (EN ISO 12185)
Solubility(ies)	The product has poor water-solubility. < 50 mg/l @ 20°C
Partition coefficient	log Kow: > 3
Auto-ignition temperature	~ 220°C Estimated value.
Decomposition Temperature	-
Viscosity	Kinematic viscosity ≤ 4,5 mm ² /s @ 40°C (EN ISO 3104).
Explosive properties	Not considered to be explosive.
Oxidising properties	Does not meet the criteria for classification as oxidising.
<u>9.2. Other information</u>	
Other information	Not known.

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity There are no known reactivity hazards associated with this product.

10.2. Chemical stability

Stability Stable at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions No potentially hazardous reactions known.

10.4. Conditions to avoid

Conditions to avoid Keep away from heat, sparks and open flame.

10.5. Incompatible materials

Materials to avoid Oxidising agents.

10.6. Hazardous decomposition products

Hazardous decomposition products Does not decompose when used and stored as recommended.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Toxicological effects Harmful if inhaled.

Acute toxicity - inhalation

ATE inhalation (vapours mg/l) 15.71

Skin corrosion/irritation

Diesel fuel, sulphur free; Neste Pro Diesel; Neste Futura Diesel

Skin corrosion/irritation	Fuels, diesel: Irritating to skin. (OECD 404) Renewable hydrocarbons (diesel type fraction): Not classified. (EC B4) The product irritates mucous membranes and may cause abdominal discomfort if swallowed. May cause respiratory irritation.
<u>Serious eye damage/irritation</u>	
Serious eye damage/irritation	Based on available data the classification criteria are not met. (OECD 405, EC B5)
<u>Skin sensitisation</u>	
Skin sensitisation	Based on available data the classification criteria are not met. (OECD 406, EC B6)
<u>Germ cell mutagenicity</u>	
Genotoxicity - in vitro	Based on available data the classification criteria are not met. (OECD 471, EC B10, B13/14, B17)
Genotoxicity - in vivo	Based on available data the classification criteria are not met. Fuels, diesel: (OECD 475)
<u>Carcinogenicity</u>	
Carcinogenicity	Suspected of causing cancer. Fuels, diesel: Product may contain cracked gas oil streams. Contains a substance/a group of substances which may cause cancer.
<u>Reproductive toxicity</u>	
Reproductive toxicity - fertility	Based on available data the classification criteria are not met. Renewable hydrocarbons (diesel type fraction): (OECD 416)
Reproductive toxicity - development	Based on available data the classification criteria are not met. Fuels, diesel: (OECD 414)
<u>Specific target organ toxicity - single exposure</u>	
STOT - single exposure	Not classified as a specific target organ toxicant after a single exposure.
<u>Specific target organ toxicity - repeated exposure</u>	
STOT - repeated exposure	Fuels, diesel: May cause damage to organs through prolonged or repeated exposure. (OECD 410, 411, 413) Renewable hydrocarbons (diesel type fraction): Not classified. (OECD 408)
<u>Aspiration hazard</u>	
Aspiration hazard	May be fatal if swallowed and enters airways. Entry into the lungs following ingestion or vomiting may cause chemical pneumonitis.

Toxicological information on ingredients.

Fuels, diesel

Acute toxicity - oral

Notes (oral LD₅₀) LD₅₀ > 5000 mg/kg, Oral, Rat (OECD 401, 420)

Acute toxicity - dermal

Notes (dermal LD₅₀) LD₅₀ > 4300 mg/kg, Dermal, Rabbit (OECD 434)

Acute toxicity - inhalation

Notes (inhalation LC₅₀) LC₅₀ 3,6 - 5,4 mg/l, Inhalation, (4h), Rat (OECD 403)

ATE inhalation (vapours mg/l) 11.0

Renewable hydrocarbons (diesel type fraction)

Acute toxicity - oral

Notes (oral LD₅₀) LD₅₀ >2000 mg/kg, Oral, Rat (EC B1 tris)

Diesel fuel, sulphur free; Neste Pro Diesel; Neste Futura Diesel

Acute toxicity - dermal

Notes (dermal LD₅₀) LD₅₀ > 2000 mg/kg, Dermal, Rat (EC B3)

SECTION 12: Ecological Information

12.1. Toxicity

Toxicity Toxic to aquatic life with long lasting effects.

Ecological information on ingredients.

Fuels, diesel

Acute aquatic toxicity

Acute toxicity - fish	LL ₅₀ , 96 hours: 21 mg/l, Oncorhynchus mykiss (Rainbow trout) NOEL, 96 hours: 10 mg/l, Oncorhynchus mykiss (Rainbow trout) WAF (OECD 203, EC C.1)
Acute toxicity - aquatic invertebrates	EL50, 48 hours: 68 mg/l, Daphnia magna NOEL, 48 hours: 46 mg/l, Daphnia magna WAF (OECD 202, EC C.2)
Acute toxicity - aquatic plants	EbL50, 72 hours: 10 mg/l, Pseudokirchneriella subcapitata NOEL, 72 hours: 1 mg/l, Pseudokirchneriella subcapitata WAF (OECD 201, EC C.3)
Acute toxicity - microorganisms	EL50, 40 hours: > 1000 mg/l, Micro-organisms (wastewater sludge) NOEL, 40 hours: 3,22 mg/l, Micro-organisms (wastewater sludge) (QSAR)

Chronic aquatic toxicity

Chronic toxicity - fish early life stage	NOEL, 14 days: 0,08 mg/l, Oncorhynchus mykiss (Rainbow trout) (QSAR)
Chronic toxicity - aquatic invertebrates	NOEL, 21 days: 0,2 mg/l, Daphnia magna (QSAR)

Renewable hydrocarbons (diesel type fraction)

Acute aquatic toxicity

Acute toxicity - fish	LL ₅₀ , 96 hours: > 1000 mg/l, WAF (OECD 203)
Acute toxicity - aquatic invertebrates	EL50, 48 hours: > 100 mg/l, WAF (OECD 202)
Acute toxicity - aquatic plants	EL50, 72 hours: > 100 mg/l, Algae WAF (OECD 201)
Acute toxicity - microorganisms	EC ₅₀ , 30-180 minutes: > 1000 mg/l, Micro-organisms (wastewater sludge) (OECD 209)

Chronic aquatic toxicity

Diesel fuel, sulphur free; Neste Pro Diesel; Neste Futura Diesel

Chronic toxicity - aquatic invertebrates	NOEC, 21 days: 1 mg/l, LOEC, 21 days: 3,2 mg/l, WAF (OECD 211) Sediment organisms NOEC, 10 days: 373 mg/kg, LOEC, 10 days: 1165 mg/kg, LC ₅₀ , 10 days: 1200 mg/kg, (OSPAR Protocols, Part A: Sediment Bioassay, 2005)
---	--

12.2. Persistence and degradability

Persistence and degradability The product contains volatile substances which may spread in the atmosphere. Can be photodegraded in the atmosphere.

Stability (hydrolysis) No significant reaction in water.

Ecological information on ingredients.

Fuels, diesel

Biodegradation	Inherently biodegradable. (OECD 301F)
-----------------------	--

Renewable hydrocarbons (diesel type fraction)

Biodegradation	Rapidly degradable (OECD 301B)
-----------------------	-----------------------------------

12.3. Bioaccumulative potential

Bioaccumulative potential Possibly bioaccumulative.

Partition coefficient log Kow: > 3

12.4. Mobility in soil

Mobility Evaporates slowly. The product has poor water-solubility. Product can penetrate soil until reaching the surface of ground water. The product contains substances which are bound to particulate matter and are retained in soil.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment This product does not contain any substances classified as PBT or vPvB.

12.6. Other adverse effects

Other adverse effects Product causes fouling, and direct contact produces harmful effects e.g. to birds and vegetation. Adsorbed hydrocarbon residues can be harmful to sediment organisms.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal methods Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority. When handling waste, the safety precautions applying to handling of the product should be considered. Care should be taken when handling emptied containers that have not been thoroughly cleaned or rinsed out.

SECTION 14: Transport information

14.1. UN number

UN No. (ADR/RID) 1202

Diesel fuel, sulphur free; Neste Pro Diesel; Neste Futura Diesel

14.2. UN proper shipping name

Proper shipping name (ADR/RID) UN 1202 DIESEL FUEL

14.3. Transport hazard class(es)

ADR/RID class 3

14.4. Packing group

ADR/RID packing group III

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant
MARINE POLLUTANT

14.6. Special precautions for user

Tunnel restriction code (D/E)

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code When containing more than 1% but less than 75% of petroleum oil, the bio-fuel blend is subject to Annex II of MARPOL. (MEPC.1/Circ.761) - - - - When a flashpoint is > 60 °C, product name: Bio-fuel blends Diesel/ gas oil and Alkanes (C10-C26), linear and branched with a flash point > 60 °C (> 25% but < 99% by volume). Pollution category: Cat X Ship type: 2 - - - - When a flashpoint is ≤ 60 °C, product name: Bio-fuel blends Diesel/ gas oil and Alkanes (C10-C26), linear and branched with a flash point ≤ 60 °C (> 25% but < 99% by volume). Pollution category: Cat X Ship type: 2

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended).
Commission Regulation (EU) No 2015/830 of 28 May 2015.
Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).

15.2. Chemical safety assessment

A chemical safety assessment has been carried out.

SECTION 16: Other information

Abbreviations and acronyms used in the safety data sheet ACGIH = American Conference of Governmental Industrial Hygienists
TLV = Treshold Limit Value
TWA = Time-Weighted Average
DNEL = Derived No-Effect Level
PNEC = Predicted No-Effect Concentration
WAF = Water Accommodated Fraction

Key literature references and sources for data Regulations, databases, literature, own research. CONCAWE Report 10/14: Hazard classification and labelling of petroleum substances in the EEA - 2014. Chemical Safety Report Fuels, diesel 2017. Chemical Safety Report Renewable hydrocarbons (diesel type fraction), 2016.

Training advice DO NOT SIPHON PRODUCT BY MOUTH SUCTION.

Diesel fuel, sulphur free; Neste Pro Diesel; Neste Futura Diesel

Revision comments	Updated, sections: Exposure scenarios NOTE: Lines within the margin indicate significant changes from the previous revision.
Revision date	30/07/2018
Supersedes date	13/12/2017
SDS number	5634
Hazard statements in full	H226 Flammable liquid and vapour. H304 May be fatal if swallowed and enters airways. H315 Causes skin irritation. H332 Harmful if inhaled. H351 Suspected of causing cancer. H373 May cause damage to organs through prolonged or repeated exposure. H411 Toxic to aquatic life with long lasting effects.

Exposure scenario

Use of Substance as Intermediate

Identification

Product name	Fuels, diesel
CAS number	68334-30-5
Version number	2018
Es reference	ES01b

1. Title of exposure scenario

Main title	Use of Substance as Intermediate
Process scope	Use of substance as an intermediate (not related to Strictly Controlled Conditions). Includes recycling/recovery, material transfers, storage, sampling, associated laboratory activities, maintenance and loading (including marine vessel/barge, road/rail car and bulk container).
Sector of use	SU8 Manufacture of bulk, large-scale chemicals (including petroleum products) SU9 Manufacture of fine chemicals
Environment	
Environmental release category	ERC6a Industrial use resulting in manufacture of another substance (use of intermediates).
SPERC	ESVOC SpERC 6.1a.v1
Worker	
Process category	PROC1 Use in closed process, no likelihood of exposure. PROC2 Use in closed, continuous process with occasional controlled exposure PROC3 Use in closed batch process (synthesis or formulation). PROC4 Use in batch and other process (synthesis) where opportunity for exposure arises. PROC8a Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities. PROC8b Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities. PROC15 Use as laboratory reagent.

2. Conditions of use affecting exposure (Industrial - Environment 1)

Product characteristics

Substance is complex UVCB. Predominantly hydrophobic.

Amounts used

Fraction of EU tonnage used in region: 0.1
Regional use tonnage: 1 000 000 tonnes/year
Fraction of Regional tonnage used locally: 0.015
Annual site tonnage: 15 000 tonnes
Maximum daily site tonnage: 50 tonne/day

Frequency and duration of use

Continuous release.
Emission days: 300 days/year

Other given operational conditions affecting environmental exposure

Emission factor - air Release fraction to air from process (initial release prior to RMM): 0.001

Use of Substance as Intermediate

Emission factor - water Release fraction to wastewater from process (initial release prior to RMM): 2.4E-04

Emission factor - soil Release fraction to soil from process (initial release prior to RMM): 0.001

Environmental factors not influenced by risk management measures

Dilution Local freshwater dilution factor: 10
Local marine water dilution factor: 100

Risk management measures

Good practice Common practices vary across sites, thus conservative process release estimates used.

Risk from environmental exposure is driven by freshwater sediment. Prevent discharge of undissolved substance to or recover from onsite waste water. If discharging to domestic sewage treatment plant, no onsite wastewater treatment required.

STP details Estimated substance removal from wastewater via domestic sewage treatment: 94.9%
Removal efficiency (total): 94.9%
Maximum allowable site tonnage (M_{safe}), based on release following total wastewater treatment removal: 5.5E+04 kg/day
Assumed domestic sewage treatment plant flow (m³/day): 2000.

Technical onsite conditions and measures to reduce or limit discharges to air, water and soil

Air Treat air emission to provide a typical removal efficiency of 80%.

Water Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of (%): ≥ 94.4 If discharging to domestic sewage treatment plant, provide the required onsite wastewater removal efficiency of (%): ≥ 0. Prevent discharge of undissolved substance to or recover from onsite waste water.

Soil Do not apply industrial sludge to natural soils. Sludge should be incinerated, contained or reclaimed.

Conditions and measures related to external treatment of waste for disposal

Waste treatment This substance is consumed during use and no waste of the substance is generated.

Conditions and measures related to external recovery of waste

Recovery method This substance is consumed during use and no waste of the substance is generated.

2. Conditions of use affecting exposure (Workers - Health 1)

Product characteristics

Physical state Liquid With potential for aerosol generation

Vapour pressure Vapour pressure < 0.5 kPa at STP.

Concentration details Covers percentage substance in the product up to 100% (unless stated differently).

Frequency and duration of use

Covers daily exposures up to 8 hours (unless stated differently).

Other given operational conditions affecting workers exposure

Setting Assumes a good basic standard of occupational hygiene is implemented.

Temperature Operation is carried out at elevated temperature (> 20°C above ambient temperature).

Organisational measures to prevent/limit releases, dispersion and exposure

Use of Substance as Intermediate

Organisational measures

General measures applicable to all activities Control any potential exposure using measures such as contained or enclosed systems, properly designed and maintained facilities and a good standard of general ventilation. Drain down systems and clear transfer lines prior to breaking containment. Drain down and flush equipment where possible prior to maintenance. Where there is potential for exposure: Ensure relevant staff are informed of the nature of exposure and aware of basic actions to minimise exposures; Ensure suitable personal protective equipment is available; Clear up spills and dispose of waste in accordance with regulatory requirements; monitor effectiveness of control measures; consider the need for health surveillance; identify and implement corrective actions. . General measures (skin irritants) Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent/minimise exposures and to report any skin problems that may develop.

Risk management measures

General exposures (closed systems)
Handle substance within a closed system.

General exposures (open systems)
Wear suitable gloves tested to EN374.

Process sampling
No other specific measures identified.

Bulk closed loading and unloading
Handle substance within a closed system.
Wear suitable gloves tested to EN374.

Bulk open loading and unloading
Wear suitable gloves tested to EN374.

Equipment cleaning and maintenance
Drain down and flush system prior to equipment break-in or maintenance.
Wear chemically-resistant gloves (tested to EN374) in combination with 'basic' employee training.

Laboratory activities
No other specific measures identified.

Bulk product storage
Handle substance within a closed system.

3. Exposure estimation (Environment 1)

Assessment method

Used Petrorisk model. (Hydrocarbon Block Method)

Risk-driving RCR - air compartment driven $RCR(\text{air}) \leq 0.0086$

Risk-driving RCR - water compartment driven $RCR(\text{water}) \leq 0.91$

4. Guidance to check compliance with the exposure scenario (Environment 1)

Use of Substance as Intermediate

Guidance is based on assumed operating conditions which may not be applicable to all sites, thus, scaling may be necessary to define appropriate site-specific risk management measures. Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination. Required removal efficiency for air can be achieved using onsite technologies, either alone or in combination. Further details on scaling and control technologies are provided in SpERC factsheet (<http://cefic.org/en/reach-for-industries-libraries.html>).

3. Exposure estimation (Health 1)

Assessment method

The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated

Available hazard data do not enable the derivation of a DNEL for dermal irritant effects. Available hazard data do not support the need for a DNEL to be established for other health effects. Qualitative approach used to conclude safe use.

4. Guidance to check compliance with the exposure scenario (Health 1)

Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented. Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

Exposure scenario Distribution of Substance

Identification

Product name	Fuels, diesel
CAS number	68334-30-5
Version number	2018
Es reference	ES01a

1. Title of exposure scenario

Main title	Distribution of Substance
Process scope	Loading (including marine vessel/barge, rail/road car and IBC loading) and repacking (including drums and small packs) of substance, including its sampling, storage, unloading distribution and associated laboratory activities.

Environment

Environmental release category	ERC4 Industrial use of processing aids in processes and products, not becoming part of articles. ERC5 Industrial use resulting in inclusion into or onto a matrix. ERC6a Industrial use resulting in manufacture of another substance (use of intermediates). ERC6b Industrial use of reactive processing aids. ERC6c Industrial use of monomers for manufacture of thermoplastics. ERC6d Industrial use of process regulators for polymerisation processes in production of resins, rubbers, polymers. ERC7 Industrial use of substances in closed systems.
---------------------------------------	--

SPERC	ESVOC SpERC 1.1b.v1
--------------	---------------------

Worker

Process category	PROC1 Use in closed process, no likelihood of exposure. PROC2 Use in closed, continuous process with occasional controlled exposure PROC3 Use in closed batch process (synthesis or formulation). PROC4 Use in batch and other process (synthesis) where opportunity for exposure arises. PROC8a Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities. PROC8b Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities. PROC9 Transfer of substance or preparation into small containers (dedicated filling line, including weighing). PROC15 Use as laboratory reagent.
-------------------------	---

2. Conditions of use affecting exposure (Industrial - Environment 1)

Product characteristics

Substance is complex UVCB. Predominantly hydrophobic.

Amounts used

Fraction of EU tonnage used in region: 0.1
Regional use tonnage: 31 000 000 tonnes/year
Fraction of Regional tonnage used locally: 0.002
Annual site tonnage: 61 000 tonnes
Maximum daily site tonnage: 200 tonne/day

Distribution of Substance

Frequency and duration of use

Continuous release.
Emission days: 300 days/year

Other given operational conditions affecting environmental exposure

Emission factor - air Release fraction to air from process (initial release prior to RMM): 0.001
Emission factor - water Release fraction to wastewater from process (initial release prior to RMM): 0.00001
Emission factor - soil Release fraction to soil from process (initial release prior to RMM): 0.00001

Environmental factors not influenced by risk management measures

Dilution Local freshwater dilution factor: 10
Local marine water dilution factor: 100

Risk management measures

Good practice Common practices vary across sites, thus conservative process release estimates used.
Risk from environmental exposure is driven by freshwater sediment.

STP details Estimated substance removal from wastewater via domestic sewage treatment: 94.9%
Removal efficiency (total): 94.9%
Maximum allowable site tonnage (M_{safe}), based on release following total wastewater treatment removal: 1000 tonne/day
2000.
Assumed domestic sewage treatment plant flow (m³/day):

Technical onsite conditions and measures to reduce or limit discharges to air, water and soil

Air Treat air emission to provide a typical removal efficiency of 90%.
Water Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of (%): 74.3. If discharging to domestic sewage treatment plant, no onsite wastewater treatment required.
Soil Do not apply industrial sludge to natural soils. Sludge should be incinerated, contained or reclaimed.

Conditions and measures related to external treatment of waste for disposal

Waste treatment External treatment and disposal of waste should comply with applicable local and/or national regulations.

Conditions and measures related to external recovery of waste

Recovery method External recovery and recycling of waste should comply with applicable local and/or national regulations.

2. Conditions of use affecting exposure (Workers - Health 1)

Product characteristics

Physical state Liquid With potential for aerosol generation
Vapour pressure Vapour pressure < 0.5 kPa at STP.
Concentration details Covers percentage substance in the product up to 100% (unless stated differently).

Frequency and duration of use

Covers daily exposures up to 8 hours (unless stated differently).

Other given operational conditions affecting workers exposure

Distribution of Substance

Setting	Assumes a good basic standard of occupational hygiene is implemented.
Temperature	Assumes use at not more than 20°C above ambient temperature, unless stated differently.
<u>Organisational measures to prevent/limit releases, dispersion and exposure</u>	
Organisational measures	General measures applicable to all activities Control any potential exposure using measures such as contained or enclosed systems, properly designed and maintained facilities and a good standard of general ventilation. Drain down systems and clear transfer lines prior to breaking containment. Drain down and flush equipment where possible prior to maintenance. Where there is potential for exposure: Ensure relevant staff are informed of the nature of exposure and aware of basic actions to minimise exposures; Ensure suitable personal protective equipment is available; Clear up spills and dispose of waste in accordance with regulatory requirements; monitor effectiveness of control measures; consider the need for health surveillance; identify and implement corrective actions. . General measures (skin irritants) Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent/minimise exposures and to report any skin problems that may develop.
<u>Risk management measures</u>	
	General exposures (closed systems) Handle substance within a closed system. .
	General exposures (open systems) Wear suitable gloves tested to EN374. .
	Process sampling No other specific measures identified. .
	Laboratory activities No other specific measures identified. .
	Bulk closed loading and unloading Handle substance within a closed system. Wear suitable gloves tested to EN374. .
	Bulk open loading and unloading Wear suitable gloves tested to EN374. .
	Drum and small package filling Wear suitable gloves tested to EN374. .
	Equipment cleaning and maintenance Drain down and flush system prior to equipment break-in or maintenance. Wear chemically-resistant gloves (tested to EN374) in combination with 'basic' employee training. .
	Storage Handle substance within a closed system.

3. Exposure estimation (Environment 1)

Assessment method Used Petrorisk model. (Hydrocarbon Block Method)

Distribution of Substance

Risk-driving RCR - air compartment driven $\text{RCR}(\text{air}) \leq 0.024$ Risk-driving RCR - water compartment driven $\text{RCR}(\text{water}) \leq 0.20$

4. Guidance to check compliance with the exposure scenario (Environment 1)

Guidance is based on assumed operating conditions which may not be applicable to all sites, thus, scaling may be necessary to define appropriate site-specific risk management measures. Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination. Required removal efficiency for air can be achieved using onsite technologies, either alone or in combination. Further details on scaling and control technologies are provided in SpERC factsheet (<http://cefic.org/en/reach-for-industries-libraries.html>).

3. Exposure estimation (Health 1)

Assessment method

The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated

Available hazard data do not enable the derivation of a DNEL for dermal irritant effects. Available hazard data do not support the need for a DNEL to be established for other health effects. Qualitative approach used to conclude safe use.

4. Guidance to check compliance with the exposure scenario (Health 1)

Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented. Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

Exposure scenario

Use as a Fuel - Industrial

Identification

Product name	Fuels, diesel
CAS number	68334-30-5
Version number	2018
Es reference	ES12a

1. Title of exposure scenario

Main title	Use as a Fuel - Industrial
Process scope	Covers the use as a fuel (or fuel additive) and includes activities associated with its transfer, use, equipment maintenance and handling of waste.

Environment

Environmental release category ERC7 Industrial use of substances in closed systems.

SPERC ESVOC SpERC 7.12a.v1

Worker

Process category

PROC1 Use in closed process, no likelihood of exposure.
 PROC2 Use in closed, continuous process with occasional controlled exposure
 PROC3 Use in closed batch process (synthesis or formulation).
 PROC8a Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities.
 PROC8b Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities.
 PROC16 Using material as fuel sources, limited exposure to unburned product to be expected.

2. Conditions of use affecting exposure (Industrial - Environment 1)

Product characteristics

Substance is complex UVCB. Predominantly hydrophobic.

Amounts used

Fraction of EU tonnage used in region: 0.1
 Regional use tonnage: 3 700 000 tonnes/year
 Fraction of Regional tonnage used locally: 0.4
 Annual site tonnage: 1 500 000 tonnes
 Maximum daily site tonnage: 5,000 tonne/day

Frequency and duration of use

Continuous release.
 Emission days: 300 days/year

Other given operational conditions affecting environmental exposure

Emission factor - air	Release fraction to air from process (initial release prior to RMM): 0.005
Emission factor - water	Release fraction to wastewater from process (initial release prior to RMM): 2.4E-06
Emission factor - soil	Release fraction to soil from process (initial release prior to RMM): 0

Use as a Fuel - Industrial

Environmental factors not influenced by risk management measures

Dilution Local freshwater dilution factor: 10
Local marine water dilution factor: 100

Risk management measures

Good practice Common practices vary across sites, thus conservative process release estimates used.
Risk from environmental exposure is driven by freshwater sediment.

STP details Estimated substance removal from wastewater via domestic sewage treatment: 94.9%
Removal efficiency (total): 98.7%
Maximum allowable site tonnage (M_{safe}), based on release following total wastewater treatment removal: 5 000 tonne/day
Assumed domestic sewage treatment plant flow (m³/day): 2000.

Technical onsite conditions and measures to reduce or limit discharges to air, water and soil

Air Treat air emission to provide a typical removal efficiency of 95%.

Water Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of (%): ≥ 94.4. If discharging to domestic sewage treatment plant, provide the required onsite wastewater removal efficiency of (%): ≥ 0.

Soil Do not apply industrial sludge to natural soils. Sludge should be incinerated, contained or reclaimed.

Conditions and measures related to external treatment of waste for disposal

Waste treatment Combustion emissions limited by required exhaust emission controls. Combustion emissions considered in regional exposure assessment. External treatment and disposal of waste should comply with applicable local and/or national regulations.

Conditions and measures related to external recovery of waste

Recovery method This substance is consumed during use and no waste of the substance is generated.

2. Conditions of use affecting exposure (Workers - Health 1)

Product characteristics

Physical state Liquid With potential for aerosol generation

Vapour pressure Vapour pressure < 0.5 kPa at STP.

Concentration details Covers percentage substance in the product up to 100% (unless stated differently).

Frequency and duration of use

Covers daily exposures up to 8 hours (unless stated differently).

Other given operational conditions affecting workers exposure

Setting Assumes a good basic standard of occupational hygiene is implemented.

Temperature Assumes use at not more than 20°C above ambient temperature, unless stated differently.

Organisational measures to prevent/limit releases, dispersion and exposure

Use as a Fuel - Industrial

Organisational measures

General measures applicable to all activities Control any potential exposure using measures such as contained or enclosed systems, properly designed and maintained facilities and a good standard of general ventilation. Drain down systems and clear transfer lines prior to breaking containment. Drain down and flush equipment where possible prior to maintenance. Where there is potential for exposure: Ensure relevant staff are informed of the nature of exposure and aware of basic actions to minimise exposures; Ensure suitable personal protective equipment is available; Clear up spills and dispose of waste in accordance with regulatory requirements; monitor effectiveness of control measures; consider the need for health surveillance; identify and implement corrective actions. . General measures (skin irritants) Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent/minimise exposures and to report any skin problems that may develop.

Risk management measures

Bulk transfers

Wear suitable gloves tested to EN374.

.

Drum/batch transfers

Wear suitable gloves tested to EN374.

.

Use as a fuel

(closed systems)

No other specific measures identified.

.

Equipment cleaning and maintenance

Drain down and flush system prior to equipment break-in or maintenance.

Wear chemically-resistant gloves (tested to EN374) in combination with 'basic' employee training.

.

Storage

Handle substance within a closed system.

3. Exposure estimation (Environment 1)

Assessment method

Used Petrorisk model. (Hydrocarbon Block Method)

Risk-driving RCR - air compartment driven $RCR(\text{air}) \leq 0.028$

Risk-driving RCR - water compartment driven $RCR(\text{water}) \leq 0.91$

4. Guidance to check compliance with the exposure scenario (Environment 1)

Guidance is based on assumed operating conditions which may not be applicable to all sites, thus, scaling may be necessary to define appropriate site-specific risk management measures. Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination. Required removal efficiency for air can be achieved using onsite technologies, either alone or in combination. Further details on scaling and control technologies are provided in SpERC factsheet (<http://cefic.org/en/reach-for-industries-libraries.html>).

3. Exposure estimation (Health 1)

Assessment method

The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated

Use as a Fuel - Industrial

Available hazard data do not enable the derivation of a DNEL for dermal irritant effects.
Available hazard data do not support the need for a DNEL to be established for other health effects. Qualitative approach used to conclude safe use.

4. Guidance to check compliance with the exposure scenario (Health 1)

Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented. Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

Exposure scenario

Use as a Fuel - Professional

Identification

Product name	Fuels, diesel
CAS number	68334-30-5
Version number	2018
Es reference	ES12b

1. Title of exposure scenario

Main title	Use as a Fuel - Professional
Process scope	Covers the use as a fuel (or fuel additive) and includes activities associated with its transfer, use, equipment maintenance and handling of waste.

Environment

Environmental release category	ERC9a Wide dispersive indoor use of substances in closed systems. ERC9b Wide dispersive outdoor use of substances in closed systems.
---------------------------------------	---

SPERC	ESVOC SpERC 9.12b.v1
--------------	----------------------

Worker

Process category	PROC1 Use in closed process, no likelihood of exposure. PROC2 Use in closed, continuous process with occasional controlled exposure PROC3 Use in closed batch process (synthesis or formulation). PROC8a Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities. PROC8b Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities. PROC16 Using material as fuel sources, limited exposure to unburned product to be expected.
-------------------------	--

2. Conditions of use affecting exposure (Industrial - Environment 1)

Product characteristics

Substance is complex UVCB. Predominantly hydrophobic.

Amounts used

Fraction of EU tonnage used in region: 0.1
Regional use tonnage: 6 900 000 tonnes/year
Fraction of Regional tonnage used locally: 0.0005
Annual site tonnage: 3 400 tonnes
Maximum daily site tonnage: 9.4 tonne/day

Frequency and duration of use

Continuous release.
Emission days: 365 days/year

Other given operational conditions affecting environmental exposure

Emission factor - air	Release fraction to air from wide dispersive use (regional only): 0.001
Emission factor - water	Release fraction to wastewater from wide dispersive use: 0.00001
Emission factor - soil	Release fraction to soil from wide dispersive use (regional only): 0.00001

Use as a Fuel - Professional

Environmental factors not influenced by risk management measures

Dilution Local freshwater dilution factor: 10
Local marine water dilution factor: 100

Risk management measures

Good practice Common practices vary across sites, thus conservative process release estimates used.
Risk from environmental exposure is driven by fresh water.

STP details Estimated substance removal from wastewater via domestic sewage treatment: 94.9%
Removal efficiency (total): 94.9%
Maximum allowable site tonnage (M_{safe}), based on release following total wastewater treatment removal: 1.2E+05 kg/day
Assumed domestic sewage treatment plant flow (m³/day): 2000.

Technical onsite conditions and measures to reduce or limit discharges to air, water and soil

Air Not determined.

Water Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of (%): ≥ 34.3. If discharging to domestic sewage treatment plant, no onsite wastewater treatment required.

Soil Do not apply industrial sludge to natural soils. Sludge should be incinerated, contained or reclaimed.

Conditions and measures related to external treatment of waste for disposal

Waste treatment Combustion emissions limited by required exhaust emission controls. Combustion emissions considered in regional exposure assessment. External treatment and disposal of waste should comply with applicable local and/or national regulations.

Conditions and measures related to external recovery of waste

Recovery method This substance is consumed during use and no waste of the substance is generated.

2. Conditions of use affecting exposure (Workers - Health 1)

Product characteristics

Physical state Liquid With potential for aerosol generation

Vapour pressure Vapour pressure < 0.5 kPa at STP.

Concentration details Covers percentage substance in the product up to 100% (unless stated differently).

Frequency and duration of use

Covers daily exposures up to 8 hours (unless stated differently).

Other given operational conditions affecting workers exposure

Setting Assumes a good basic standard of occupational hygiene is implemented.

Temperature Assumes use at not more than 20°C above ambient temperature, unless stated differently.

Organisational measures to prevent/limit releases, dispersion and exposure

Use as a Fuel - Professional

Organisational measures

General measures applicable to all activities Control any potential exposure using measures such as contained or enclosed systems, properly designed and maintained facilities and a good standard of general ventilation. Drain down systems and clear transfer lines prior to breaking containment. Drain down and flush equipment where possible prior to maintenance. Where there is potential for exposure: Ensure relevant staff are informed of the nature of exposure and aware of basic actions to minimise exposures; Ensure suitable personal protective equipment is available; Clear up spills and dispose of waste in accordance with regulatory requirements; monitor effectiveness of control measures; consider the need for health surveillance; identify and implement corrective actions. . General measures (skin irritants) Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent/minimise exposures and to report any skin problems that may develop.

Risk management measures

Bulk transfers

Wear suitable gloves tested to EN374.

.

Drum/batch transfers

Use drum pumps or carefully pour from container.

Wear suitable gloves tested to EN374.

.

Refuelling

Wear suitable gloves tested to EN374.

.

Use as a fuel

(closed systems)

Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour).

, or:

Ensure operation is undertaken outdoors.

.

Equipment cleaning and maintenance

Drain down and flush system prior to equipment break-in or maintenance.

Wear chemically-resistant gloves (tested to EN374) in combination with 'basic' employee training.

.

Storage

Handle substance within a closed system.

3. Exposure estimation (Environment 1)

Assessment method

Used Petrorisk model. (Hydrocarbon Block Method)

Risk-driving RCR - air compartment driven $RCR(\text{air}) \leq 0.024$

Risk-driving RCR - water compartment driven $RCR(\text{water}) \leq 0.075$

4. Guidance to check compliance with the exposure scenario (Environment 1)

Guidance is based on assumed operating conditions which may not be applicable to all sites, thus, scaling may be necessary to define appropriate site-specific risk management measures. Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination. Required removal efficiency for air can be achieved using onsite technologies, either alone or in combination. Further details on scaling and control technologies are provided in SpERC factsheet (<http://cefic.org/en/reach-for-industries-libraries.html>).

Use as a Fuel - Professional

3. Exposure estimation (Health 1)

Assessment method

The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated

Available hazard data do not enable the derivation of a DNEL for dermal irritant effects.
Available hazard data do not support the need for a DNEL to be established for other health effects. Qualitative approach used to conclude safe use.

4. Guidance to check compliance with the exposure scenario (Health 1)

Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented. Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

Exposure scenario

Use as a Fuel - Consumer

Identification

Product name	Fuels, diesel
CAS number	68334-30-5
Version number	2018
Es reference	ES12c

1. Title of exposure scenario

Main title	Use as a Fuel - Consumer
Process scope	Covers consumer uses in liquid fuels.
Product category	PC13 Fuels.
Environment	
Environmental release category	ERC9a Wide dispersive indoor use of substances in closed systems. ERC9b Wide dispersive outdoor use of substances in closed systems.
SPERC	ESVOC SpERC 9.12c.v1
Non-industrial	
Product sub-category	PC13_1 Liquid: automotive refuelling PC13_3 Liquid: garden equipment - use PC13_4 Liquid: garden equipment - refuelling PC13_6 Liquid: home space heater fuel

2. Conditions of use affecting exposure (Non-industrial - Environment 1)

Product characteristics

Substance is complex UVCB. Predominantly hydrophobic.

Amounts used

Fraction of EU tonnage used in region: 0.1
Regional use tonnage: 19 000 000 tonnes/year
Fraction of Regional tonnage used locally: 0.0005
Annual site tonnage: 9 500 tonnes
Maximum daily site tonnage: 26 tonne/day

Frequency and duration of use

Continuous release.
Emission days: 365 days/year

Other given operational conditions affecting environmental exposure

Emission factor - air	Release fraction to air from wide dispersive use (regional only): 0.001
Emission factor - water	Release fraction to wastewater from wide dispersive use: 0.00001
Emission factor - soil	Release fraction to soil from wide dispersive use (regional only): 0.00001

Environmental factors not influenced by risk management measures

Dilution	Local freshwater dilution factor: 10 Local marine water dilution factor: 100
-----------------	---

Use as a Fuel - Consumer

Risk management measures

STP details

Estimated substance removal from wastewater via domestic sewage treatment: 94.9%
 Maximum allowable site tonnage (Msafe), based on release following total wastewater treatment removal: 3.0E+05 kg/day
 Assumed domestic sewage treatment plant flow (m³/day):
 2000.

Conditions and measures related to external treatment of waste for disposal

Waste treatment

Combustion emissions limited by required exhaust emission controls. Combustion emissions considered in regional exposure assessment. External treatment and disposal of waste should comply with applicable local and/or national regulations.

Conditions and measures related to external recovery of waste

Recovery method

This substance is consumed during use and no waste of the substance is generated.

2. Conditions of use affecting exposure (Non-industrial - Health 1)

Control of Non-industrial exposure

PC13_1 Liquid: automotive refuelling

Product characteristics

Physical state

Liquid

Vapour pressure

Liquid, vapour pressure > 10 Pa (STP)

Concentration details

Covers percentage substance in the product up to 100% (unless stated differently).

Amounts used

For each use event, covers use amounts up to 37.5 kg.

Frequency and duration of use

Covers use up to 52 days/year.

Covers use up to 1 time(s)/day.

Covers exposure up to 0.05 hours per event.

Human factors not influenced by risk management

Potentially exposed body parts

Covers skin contact area up to 210.00 cm².

Other given operational conditions affecting Non-industrial exposure

Room size

Covers outdoor use. Covers use in room size of 100 m³.

Other given operational conditions affecting Non-industrial exposure

No specific risk management measure identified beyond those operational conditions stated.

2. Conditions of use affecting exposure (Non-industrial - Health 2)

Control of Non-industrial exposure

PC13_3 Liquid: garden equipment - use

Product characteristics

Physical state

Liquid

Vapour pressure

Vapour pressure > 10 kPa at STP.

Concentration details

Covers percentage substance in the product up to 100% (unless stated differently).

Use as a Fuel - Consumer

Amounts used

For each use event, covers use amounts up to 750 g.

Frequency and duration of use

Covers use up to 26 day(s)/year.
Covers use up to 1 time(s)/day.
Covers exposure up to 2 hours per event.

Human factors not influenced by risk management

Potentially exposed body parts Covers skin contact area up to 420 cm².

Other given operational conditions affecting Non-industrial exposure

Room size Covers outdoor use. Covers use in room size of 100 m³.

Other given operational conditions affecting Non-industrial exposure

No specific risk management measure identified beyond those operational conditions stated.

2. Conditions of use affecting exposure (Non-industrial - Health 3)

Control of Non-industrial exposure

PC13_4 Liquid: garden equipment - refuelling

Product characteristics

Physical state Liquid

Vapour pressure Vapour pressure > 10 kPa at STP.

Concentration details Covers percentage substance in the product up to 100% (unless stated differently).

Amounts used

For each use event, covers use amounts up to 750 g.

Frequency and duration of use

Covers use up to 26 day(s)/year.
Covers use up to 1 time(s)/day.
Covers exposure up to 0.03 hours per event.

Human factors not influenced by risk management

Potentially exposed body parts Covers skin contact area up to 420 cm².

Other given operational conditions affecting Non-industrial exposure

Room size Covers use in room size of 34 m³. Covers use in a one car garage (34 m³) under typical ventilation.

Other given operational conditions affecting Non-industrial exposure

No specific risk management measure identified beyond those operational conditions stated.

2. Conditions of use affecting exposure (Non-industrial - Health 4)

Control of Non-industrial exposure

PC13_6 Liquid: home space heater fuel

Product characteristics

Physical state Liquid

Use as a Fuel - Consumer

Vapour pressure Vapour pressure > 10 kPa at STP.

Concentration details Covers percentage substance in the product up to 100% (unless stated differently).

Amounts used

For each use event, covers use amounts up to 1.5 kg.

Frequency and duration of use

Covers use up to 120 day(s)/year.
Covers use up to 1 time(s)/day.
Covers exposure up to 0.03hours

Human factors not influenced by risk management

Potentially exposed body parts Covers skin contact area up to 210 cm².

Other given operational conditions affecting Non-industrial exposure

Room size Covers use in room size of 20 m³. Covers use under typical household ventilation.

Other given operational conditions affecting Non-industrial exposure

No specific risk management measure identified beyond those operational conditions stated.

3. Exposure estimation (Environment 1)

Assessment method Used Petrorisk model. (Hydrocarbon Block Method)

Risk-driving RCR - air compartment driven $RCR(\text{air}) \leq 0.024$
Risk-driving RCR - water compartment driven $RCR(\text{water}) \leq 0.085$

4. Guidance to check compliance with the exposure scenario (Environment 1)

Guidance is based on assumed operating conditions which may not be applicable to all sites, thus, scaling may be necessary to define appropriate site-specific risk management measures.

3. Exposure estimation (Health 1)

Assessment method The ECETOC TRA tool has been used to estimate consumer exposures, unless otherwise indicated. (ECETOC Report 107; Chapter R15 of IR&CSA TGD)

4. Guidance to check compliance with the exposure scenario (Health 1)

Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented. Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.