



SAFETY DATA SHEET

Marine Diesel Oil DMB grade (MDODMB); Neste Marine 0.1 Co-processed (DMB)

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name	Marine Diesel Oil DMB grade (MDODMB); Neste Marine 0.1 Co-processed (DMB)
Chemical name	Fuel oil, no 2
Product number	ID 13999
Internal identification	160365, 170050, 170051, 170700, 170704
UFI	UFI: VP6N-WAV1-791D-R3XP

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses	Distribution of substance (ES01a) Formulation & (re)packing of substances and mixtures (ES02) Use as a fuel (ES12a, ES12b)
-----------------	--

1.3. Details of the supplier of the safety data sheet

Supplier	Neste Oyj Keilaranta 21, Espoo, P.O.B. 95, FIN-00095 NESTE, FINLAND Tel. +358 10 45811 SDS@neste.com (chemical safety)
----------	---

1.4. Emergency telephone number

Emergency telephone	+61 2 9186 1132, Chemwatch: International Emergency Response Phone Number
National emergency telephone number	+358 800 147 111, +358 9 471 977, Poison Information Centre

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification EC 1272/2008 (SI 2019 No. 720)

Physical hazards	Not Classified
Health hazards	Acute Tox. 4 - H332 Skin Irrit. 2 - H315 Carc. 2 - H351 STOT RE 2 - H373 Asp. Tox. 1 - H304
Environmental hazards	Aquatic Chronic 2 - H411

2.2. Label elements

Hazard pictograms



Signal word

Danger

Marine Diesel Oil DMB grade (MDODMB); Neste Marine 0.1 Co-processed (DMB)

Hazard statements	H332 Harmful if inhaled. H315 Causes skin irritation. H351 Suspected of causing cancer. H373 May cause damage to organs through prolonged or repeated exposure. H304 May be fatal if swallowed and enters airways. H411 Toxic to aquatic life with long lasting effects.
Precautionary statements	P273 Avoid release to the environment. P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor. P331 Do NOT induce vomiting. P261 Avoid breathing mist. P280 Wear protective gloves.
Contains	Fuel oil, no. 2, Petroleum diesel/gas oil fraction, co-processed with renewable hydrocarbons of plant or animal origin
2.3. Other hazards	
Other hazards	Evaporates slowly. Risk of soil and ground water contamination. This product does not contain substances considered to have endocrine disrupting properties at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Fuel oil, no. 2 CAS number: 68476-30-2 EC number: 270-671-4	80-100%
Classification Acute Tox. 4 - H332 Skin Irrit. 2 - H315 Carc. 2 - H351 STOT RE 2 - H373 Asp. Tox. 1 - H304 Aquatic Chronic 2 - H411	
Petroleum diesel/gas oil fraction, co-processed with renewable hydrocarbons of plant or animal origin CAS number: —	0-20%
Classification Flam. Liq. 3 - H226 Acute Tox. 4 - H332 Skin Irrit. 2 - H315 Carc. 2 - H351 STOT RE 2 - H373 Asp. Tox. 1 - H304 Aquatic Chronic 2 - H411	

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

Other information	REACH registration number:, Fuel oil, no. 2: REACH 01-2119475501-42-XXXX, Petroleum diesel/gas oil fraction, co-processed with renewable hydrocarbons of plant or animal origin: REACH 01-2120091562-55-XXXX
--------------------------	--

SECTION 4: First aid measures

Marine Diesel Oil DMB grade (MDODMB); Neste Marine 0.1 Co-processed (DMB)

4.1. Description of first aid measures

Inhalation	Remove person to fresh air and keep comfortable for breathing. Get medical attention if symptoms are severe or persist.
Ingestion	Do not induce vomiting. Get medical attention immediately.
Skin contact	Remove contaminated clothing immediately and wash skin with soap and water. Get medical attention if irritation persists after washing.
Eye contact	Rinse immediately with plenty of water. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

General information	Irritating to skin. May irritate eyes. Harmful by inhalation. Entry into the lungs following ingestion or vomiting may cause chemical pneumonitis.
----------------------------	--

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor	Treat symptomatically.
-----------------------------	------------------------

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	Water spray, foam, dry powder or carbon dioxide.
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Specific hazards	Flammable liquid and vapour. Containers can burst violently or explode when heated, due to excessive pressure build-up.
Hazardous combustion products	Carbon dioxide (CO ₂). Carbon monoxide (CO).

5.3. Advice for firefighters

Protective actions during firefighting	Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk. Prevent fire extinguishing water from contaminating surface water or the ground water system.
Special protective equipment for firefighters	Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions	Avoid inhalation of vapours and contact with skin and eyes. Wear adequate protective equipment at all operations.
For emergency responders	Prevent unauthorized access. Vapours are heavier than air and may spread near ground and travel a considerable distance to a source of ignition and flash back. Eliminate all ignition sources if safe to do so. Take precautionary measures against static discharge.

6.2. Environmental precautions

Environmental precautions	Avoid release to the environment. Stop leak if safe to do so. Avoid the spillage or runoff entering drains, sewers or watercourses. Contain spillage with sand, earth or other suitable non-combustible material. Inform the relevant authorities if environmental pollution occurs (sewers, waterways, soil or air). Risk of soil and ground water contamination.
----------------------------------	--

6.3. Methods and material for containment and cleaning up

Marine Diesel Oil DMB grade (MDODMB); Neste Marine 0.1 Co-processed (DMB)

Methods for cleaning up Immediately start clean-up of the liquid and contaminated soil. Small Spillages: Absorb spillage with sand or other inert absorbent. Pay attention to the fire and health hazards caused by the product.

6.4. Reference to other sections

Reference to other sections For personal protection, see Section 8.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions The product contains volatile substances which may spread in the atmosphere. Avoid heat, flames and other sources of ignition. Take precautionary measures against static discharges. Use only outdoors or in a well-ventilated area. Avoid inhalation of vapours and contact with skin and eyes. Use personal protective equipment and/or local ventilation when needed. Do not eat, drink or smoke when using this product. Wash hands and any other contaminated areas of the body with soap and water before leaving the work site. During tank operations follow special instructions (risk of oxygen displacement and hydrocarbons).

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Flammable liquid storage. Store in accordance with local regulations. Store in a demarcated bunded area to prevent release to drains and/or watercourses. Only store in correctly labelled containers. Use containers made of the following materials: Mild steel. Stainless steel.

7.3. Specific end use(s)

Specific end use(s) Not known.

SECTION 8: Exposure controls/Personal protection

8.1. Control parameters

Ingredient comments The individual limit values can be applied for the hydrocarbons. Diesel fuel as total hydrocarbons; ACGIH TLV®-TWA (8h) 100 mg/m³ (IFV).

PNEC Not available.

Fuel oil, no. 2 (CAS: 68476-30-2)

DNEL Workers - Inhalation; Short term systemic effects: 4300 mg/m³, (15 min), Aerosol
 Workers - Inhalation; Long term systemic effects: 68 mg/m³, (8h), Aerosol
 Workers - Dermal; Long term systemic effects: 2,9 mg/kg, bw, (8h)
 Consumer - Inhalation; Short term systemic effects: 2600 mg/m³, (15 min), Aerosol
 Consumer - Inhalation; Long term systemic effects: 20 mg/m³, (24h), Aerosol
 Consumer - Dermal; Long term systemic effects: 1,3 mg/kg, bw, (24h)

8.2. Exposure controls

Appropriate engineering controls Provide adequate ventilation. Use personal protective equipment and/or local ventilation when needed. Handle in accordance with good industrial hygiene and safety practice. During tank operations follow special instructions (risk of oxygen displacement and hydrocarbons).

Eye/face protection Spectacles.

Hand protection Wear protective gloves. It is recommended that gloves are made of the following material: Nitrile rubber. Polyvinyl chloride (PVC). The breakthrough time for any glove material may be different for different glove manufacturers. Protective gloves according to standard EN 374. Change protective gloves regularly.

Other skin and body protection Wear anti-static protective clothing if there is a risk of ignition from static electricity.

Marine Diesel Oil DMB grade (MDODMB); Neste Marine 0.1 Co-processed (DMB)

Respiratory protection Respiratory protection must be used if the airborne contamination exceeds the recommended occupational exposure limit. Wear a respirator fitted with the following cartridge: Combination filter, type A2/P3. Filter must be changed often enough. Gas and combination filter cartridges suitable for intended use should be used.

Environmental exposure controls Store in a demarcated bunded area to prevent release to drains and/or watercourses.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	Liquid.
Colour	Yellowish. Brownish.
Odour	Hydrocarbons.
Odour threshold	-
pH	-
Melting point	Pour point -6 ... 10°C (ISO 3016)
Initial boiling point and range	150...420°C
Flash point	≥ 60°C (EN ISO 2719)
Upper/lower flammability or explosive limits	Lower flammable/explosive limit: 1 % Estimated value. Upper flammable/explosive limit: 6 % Estimated value.
Vapour pressure	< 1 kPa @ 38°C
Vapour density	-
Relative density	≤ 0,9 @ 15°C (EN ISO 12185, ISO 3675)
Solubility(ies)	The product has poor water-solubility. < 50 mg/l @ 20°C
Partition coefficient	log Kow: ≥ 4
Auto-ignition temperature	~ 250°C
Decomposition Temperature	-
Viscosity	Kinematic viscosity 2,0...11,0 mm ² /s @ 40°C (EN ISO 3104).
Explosive properties	Not considered to be explosive.
Oxidising properties	Does not meet the criteria for classification as oxidising.

9.2. Other information

Other information Not known.

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity There are no known reactivity hazards associated with this product.

10.2. Chemical stability

Stability Stable at normal ambient temperatures and when used as recommended.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions No potentially hazardous reactions known.

Marine Diesel Oil DMB grade (MDODMB); Neste Marine 0.1 Co-processed (DMB)

10.4. Conditions to avoid

Conditions to avoid Keep away from heat, sparks and open flame.

10.5. Incompatible materials

Materials to avoid Oxidising agents.

10.6. Hazardous decomposition products

Hazardous decomposition products Does not decompose when used and stored as recommended.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Toxicological effects Harmful if inhaled.

Acute toxicity - inhalation

ATE inhalation (vapours mg/l) 11.0

Skin corrosion/irritation

Skin corrosion/irritation Irritating to skin. (OECD 404) The product irritates mucous membranes and may cause abdominal discomfort if swallowed. May cause respiratory irritation.

Serious eye damage/irritation

Serious eye damage/irritation Based on available data the classification criteria are not met. (OECD 405)

Skin sensitisation

Skin sensitisation Based on available data the classification criteria are not met. (OECD 406)

Germ cell mutagenicity

Genotoxicity - in vitro Based on available data the classification criteria are not met. (OECD 471)

Genotoxicity - in vivo Based on available data the classification criteria are not met. (OECD 475)

Carcinogenicity

Carcinogenicity Suspected of causing cancer. Product may contain cracked gas oil streams. Contains a substance/a group of substances which may cause cancer.

Reproductive toxicity

Reproductive toxicity - development Based on available data the classification criteria are not met. (OECD 414)

Specific target organ toxicity - single exposure

STOT - single exposure Not classified as a specific target organ toxicant after a single exposure.

Specific target organ toxicity - repeated exposure

STOT - repeated exposure May cause damage to organs through prolonged or repeated exposure. (OECD 410, 411, 413)

Aspiration hazard

Aspiration hazard May be fatal if swallowed and enters airways. Entry into the lungs following ingestion or vomiting may cause chemical pneumonitis.

General information

This product does not contain substances considered to have endocrine disrupting properties at levels of 0.1% or higher.

Toxicological information on ingredients.

Marine Diesel Oil DMB grade (MDODMB); Neste Marine 0.1 Co-processed (DMB)

Fuel oil, no. 2

Acute toxicity - oral

Notes (oral LD₅₀) LD₅₀ > 5000 mg/kg, Oral, Rat (OECD 401, 420)

Acute toxicity - dermal

Notes (dermal LD₅₀) LD₅₀ > 4300 mg/kg, Dermal, Rabbit (OECD 434)

Acute toxicity - inhalation

Notes (inhalation LC₅₀) LC₅₀ 3,6 - 5,4 mg/l, Inhalation, Rat (4h) (OECD 403)

ATE inhalation (vapours mg/l) 11.0

Petroleum diesel/gas oil fraction, co-processed with renewable hydrocarbons of plant or animal origin

Acute toxicity - inhalation

ATE inhalation (vapours mg/l) 11.0

SECTION 12: Ecological information

12.1. Toxicity

Toxicity Toxic to aquatic life with long lasting effects.

Ecological information on ingredients.

Fuel oil, no. 2

Acute aquatic toxicity

Acute toxicity - fish LL₅₀, 96 hours: 21 mg/l, Oncorhynchus mykiss (Rainbow trout)
NOEL, 96 hours: 10 mg/l, Oncorhynchus mykiss (Rainbow trout)
WAF (OECD 203, EU C.1)

Acute toxicity - aquatic invertebrates EL₅₀, 48 hours: 68 mg/l, Daphnia magna
NOEL, 48 hours: 46 mg/l, Daphnia magna
WAF (OECD 202, EU C.2)

Acute toxicity - aquatic plants EbL₅₀, 72 hours: 10 mg/l, Pseudokirchneriella subcapitata
NOEL, 72 hours: 1 mg/l, Pseudokirchneriella subcapitata
WAF (OECD 201, EU C.3)

Acute toxicity - microorganisms EL₅₀, 40 hours: > 1000 mg/l, Micro-organisms (wastewater sludge)
NOEL, 40 hours: 3,22 mg/l, Micro-organisms (wastewater sludge) (QSAR)

Chronic aquatic toxicity

Chronic toxicity - fish early life stage NOEL, 14 days: 0,08 mg/l, Oncorhynchus mykiss (Rainbow trout) (QSAR)

Chronic toxicity - aquatic invertebrates NOEL, 21 days: 0,2 mg/l, Daphnia magna (QSAR)

12.2. Persistence and degradability

Persistence and degradability The product contains volatile substances which may spread in the atmosphere. Can be photodegraded in the atmosphere.

Stability (hydrolysis) No significant reaction in water.

Marine Diesel Oil DMB grade (MDODMB); Neste Marine 0.1 Co-processed (DMB)

Ecological information on ingredients.

Fuel oil, no. 2

Biodegradation	Inherently biodegradable. (OECD 301F)
-----------------------	--

12.3. Bioaccumulative potential

Bioaccumulative potential	Possibly bioaccumulative.
----------------------------------	---------------------------

Partition coefficient	log Kow: ≥ 4
------------------------------	-------------------

12.4. Mobility in soil

Mobility	Evaporates slowly. The product has poor water-solubility. Product can penetrate soil until reaching the surface of ground water. The product contains substances which are bound to particulate matter and are retained in soil.
-----------------	--

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment	This product does not contain any substances classified as PBT or vPvB.
---	---

12.6. Other adverse effects

Other adverse effects	Product causes fouling, and direct contact produces harmful effects e.g. to birds and vegetation. Adsorbed hydrocarbon residues can be harmful to sediment organisms.
------------------------------	---

Endocrine-disrupting properties	This product does not contain substances considered to have endocrine disrupting properties at levels of 0.1% or higher.
--	--

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal methods	Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority. When handling waste, the safety precautions applying to handling of the product should be considered. Care should be taken when handling emptied containers that have not been thoroughly cleaned or rinsed out.
-------------------------	--

Waste class	The waste code classification is to be carried out according to the European Waste Catalogue (EWC). For example: 13 07 01 fuel oil and diesel.
--------------------	---

SECTION 14: Transport information

14.1. UN number

UN No. (ADR/RID)	1202
-------------------------	------

14.2. UN proper shipping name

Proper shipping name (ADR/RID)	UN 1202 GAS OIL
---------------------------------------	-----------------

14.3. Transport hazard class(es)

ADR/RID class	3
----------------------	---

14.4. Packing group

ADR/RID packing group	III
------------------------------	-----

14.5. Environmental hazards

Marine Diesel Oil DMB grade (MDODMB); Neste Marine 0.1 Co-processed (DMB)

Environmentally hazardous substance/marine pollutant



MARINE POLLUTANT

14.6. Special precautions for user

Hazard Identification Number 30
(ADR/RID)

Tunnel restriction code (D/E)

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78
and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations EU regulatory references for the safety data sheet:
Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended)
Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended)

15.2. Chemical safety assessment

A chemical safety assessment has been carried out.

SECTION 16: Other information

Abbreviations and acronyms used in the safety data sheet ACGIH = American Conference of Governmental Industrial Hygienists
TLV = Treshold Limit Value
TWA = Time-Weighted Average

Key literature references and sources for data Regulations, databases, literature, own research. Concawe Report no. 9/15. Chemical Safety Report Fuel oil, no. 2, 2017.

Revision comments Product name change. Updated, sections: 2.3, 11.1, 12.6
NOTE: Lines within the margin indicate significant changes from the previous revision.

Revision date 17/04/2023

Supersedes date 21/07/2022

SDS number 5540

Hazard statements in full H226 Flammable liquid and vapour.
H304 May be fatal if swallowed and enters airways.
H315 Causes skin irritation.
H332 Harmful if inhaled.
H351 Suspected of causing cancer.
H373 May cause damage to organs through prolonged or repeated exposure.
H411 Toxic to aquatic life with long lasting effects.

Exposure scenario

Formulation & (re)packing of Substances and Mixtures

Identification

Product name	Fuel oil, no. 2
CAS number	68476-30-2
Version number	2017
Es reference	ES02

1. Title of exposure scenario

Main title	Formulation & (re)packing of Substances and Mixtures
Process scope	Formulation, packing and re-packing of the substance and its mixtures in batch or continuous operations, including storage, materials transfers, mixing, tableting, compression, pelletisation, extrusion, large and small scale packing, sampling, maintenance and associated laboratory activities.
<u>Environment</u>	
Environmental release category	ERC2 Formulation into mixture
SPERC	ESVOC SPERC 2.2.v1
<u>Worker</u>	
Process category	<p>PROC1 Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions</p> <p>PROC2 Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions</p> <p>PROC3 Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition</p> <p>PROC4 Chemical production where opportunity for exposure arises</p> <p>PROC5 Mixing or blending in batch processes</p> <p>PROC8a Transfer of substance or mixture (charging and discharging) at non-dedicated facilities</p> <p>PROC8b Transfer of substance or mixture (charging and discharging) at dedicated facilities</p> <p>PROC9 Transfer of substance or mixture into small containers (dedicated filling line, including weighing)</p> <p>PROC14 Tableting, compression, extrusion, pelletisation, granulation</p> <p>PROC15 Use as laboratory reagent.</p>

2. Conditions of use affecting exposure (Industrial - Environment 1)

<u>Product characteristics</u>	Substance is complex UVCB. Predominantly hydrophobic.
--------------------------------	---

<u>Amounts used</u>	<p>Fraction of EU tonnage used in region: 0.1</p> <p>Regional use tonnage: 280 000 tonnes/year</p> <p>Fraction of Regional tonnage used locally: 0.11</p> <p>Annual site tonnage: 30 000 tonnes</p> <p>Maximum daily site tonnage: 100 tonne/day</p>
---------------------	--

Frequency and duration of use

Formulation & (re)packing of Substances and Mixtures

Continuous release.
Emission days: 300 days/year

Other given operational conditions affecting environmental exposure

Emission factor - air	Release fraction to air from process (after typical onsite RMMs consistent with EU Solvent Emissions Directive requirements): 0,01
Emission factor - water	Release fraction to wastewater from process (initial release prior to RMM): 0.00002
Emission factor - soil	Release fraction to soil from process (initial release prior to RMM): 0.0001

Environmental factors not influenced by risk management measures

Dilution	Local freshwater dilution factor: 10 Local marine water dilution factor: 100
-----------------	---

Risk management measures

Good practice	Common practices vary across sites, thus conservative process release estimates used. Risk from environmental exposure is driven by freshwater sediment.
STP details	Estimated substance removal from wastewater via domestic sewage treatment: 95.2% Removal efficiency (total): 95.2% Maximum allowable site tonnage (Msafe), based on release following total wastewater treatment removal: 440 tonne/day Assumed domestic sewage treatment plant flow (m³/day): 2000.

Technical onsite conditions and measures to reduce or limit discharges to air, water and soil

Air	Treat air emission to provide the required removal efficiency of 0%.
Water	Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of (%): ≥ 78.9 . If discharging to domestic sewage treatment plant, no onsite wastewater treatment required. Prevent discharge of undissolved substance to or recover from onsite waste water.
Soil	Do not apply industrial sludge to natural soils. Sludge should be incinerated, contained or reclaimed.

Conditions and measures related to external treatment of waste for disposal

Waste treatment	External treatment and disposal of waste should comply with applicable local and/or national regulations.
------------------------	---

Conditions and measures related to external recovery of waste

Recovery method	External recovery and recycling of waste should comply with applicable local and/or national regulations.
------------------------	---

2. Conditions of use affecting exposure (Workers - Health 1)

Product characteristics

Physical state	Liquid With potential for aerosol generation
Vapour pressure	Vapour pressure < 0.5 kPa at STP.
Concentration details	Covers percentage substance in the product up to 100% (unless stated differently).

Frequency and duration of use

Covers daily exposures up to 8 hours (unless stated differently).

Other given operational conditions affecting workers exposure

Formulation & (re)packing of Substances and Mixtures

Setting	Assumes a good basic standard of occupational hygiene is implemented.
Temperature	Assumes use at not more than 20°C above ambient temperature, unless stated differently.

Organisational measures to prevent/limit releases, dispersion and exposure

Organisational measures	General measures applicable to all activities Control any potential exposure using measures such as contained or enclosed systems, properly designed and maintained facilities and a good standard of general ventilation. Drain down systems and clear transfer lines prior to breaking containment. Drain down and flush equipment where possible prior to maintenance. Where there is potential for exposure: Ensure relevant staff are informed of the nature of exposure and aware of basic actions to minimise exposures; Ensure suitable personal protective equipment is available; Clear up spills and dispose of waste in accordance with regulatory requirements; monitor effectiveness of control measures; consider the need for health surveillance; identify and implement corrective actions. . General measures (skin irritants) Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent/minimise exposures and to report any skin problems that may develop.
--------------------------------	--

Risk management measures

Formulation & (re)packing of Substances and Mixtures

General exposures (closed systems)

Handle substance within a closed system.

.

General exposures (open systems)

Wear suitable gloves tested to EN374.

.

Batch processes at elevated temperatures

Provide extract ventilation to points where emissions occur.

.

Process sampling

No other specific measures identified.

.

Bulk transfers

Handle substance within a closed system.

Wear suitable gloves tested to EN374.

.

Drum/batch transfers

Use drum pumps or carefully pour from container.

Wear chemically-resistant gloves (tested to EN374) in combination with 'basic' employee training.

.

Mixing operations

(open systems)

Provide extract ventilation to points where emissions occur.

Wear chemically-resistant gloves (tested to EN374) in combination with 'basic' employee training.

.

Production of preparations or articles by tableting, compression, extrusion, pelletisation

Wear suitable gloves tested to EN374.

.

Drum and small package filling

Wear suitable gloves tested to EN374.

.

Laboratory activities

No other specific measures identified.

.

Equipment cleaning and maintenance

Drain down and flush system prior to equipment break-in or maintenance.

Wear chemically-resistant gloves (tested to EN374) in combination with 'basic' employee training.

.

Storage

Handle substance within a closed system.

3. Exposure estimation (Environment 1)

Assessment method

Used Petrorisk model. (Hydrocarbon Block Method)

Risk-driving RCR - air compartment driven $RCR(air) \leq 0.011$

Risk-driving RCR - water compartment driven $RCR(water) \leq 0.23$

4. Guidance to check compliance with the exposure scenario (Environment 1)

Formulation & (re)packing of Substances and Mixtures

Guidance is based on assumed operating conditions which may not be applicable to all sites, thus, scaling may be necessary to define appropriate site-specific risk management measures. Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination. Required removal efficiency for air can be achieved using onsite technologies, either alone or in combination. Further details on scaling and control technologies are provided in SpERC factsheet (<http://cefic.org/en/reach-for-industries-libraries.html>).

3. Exposure estimation (Health 1)

Assessment method

The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated

Available hazard data do not enable the derivation of a DNEL for dermal irritant effects. Available hazard data do not support the need for a DNEL to be established for other health effects. Qualitative approach used to conclude safe use.

4. Guidance to check compliance with the exposure scenario (Health 1)

Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented. Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

Exposure scenario

Distribution of Substance

Identification

Product name	Fuel oil, no. 2
CAS number	68476-30-2
Version number	2017
Es reference	ES01a

1. Title of exposure scenario

Main title	Distribution of Substance
Process scope	Loading (including marine vessel/barge, rail/road car and IBC loading) and repacking (including drums and small packs) of substance, including its sampling, storage, unloading distribution and associated laboratory activities.
<u>Environment</u>	
Environmental release category	<p>ERC4 Use of non-reactive processing aid at industrial site (no inclusion into or onto article)</p> <p>ERC5 Use at industrial site leading to inclusion into/onto article</p> <p>ERC6a Use of intermediate</p> <p>ERC6b Use of reactive processing aid at industrial site (no inclusion into or onto article)</p> <p>ERC6c Use of monomer in polymerisation processes at industrial site (inclusion or not into/onto article)</p> <p>ERC6d Use of reactive process regulators in polymerisation processes at industrial site (inclusion or not into/onto article)</p> <p>ERC7 Use of functional fluid at industrial site</p>
SPERC	ESVOC SPERC 1.1b.v1
<u>Worker</u>	
Process category	<p>PROC1 Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions</p> <p>PROC2 Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions</p> <p>PROC3 Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition</p> <p>PROC4 Chemical production where opportunity for exposure arises</p> <p>PROC8a Transfer of substance or mixture (charging and discharging) at non-dedicated facilities</p> <p>PROC8b Transfer of substance or mixture (charging and discharging) at dedicated facilities</p> <p>PROC9 Transfer of substance or mixture into small containers (dedicated filling line, including weighing)</p> <p>PROC15 Use as laboratory reagent.</p>

2. Conditions of use affecting exposure (Industrial - Environment 1)

Product characteristics

Substance is complex UVCB. Predominantly hydrophobic.

Amounts used

Distribution of Substance

Fraction of EU tonnage used in region: 0.1
 Regional use tonnage: 280 000 tonnes/year
 Fraction of Regional tonnage used locally: 0.002
 Annual site tonnage: 560 tonnes
 Maximum daily site tonnage: 28 tonne/day

Frequency and duration of use

Continuous release.
 Emission days: 20 days/year

Other given operational conditions affecting environmental exposure

Emission factor - air Release fraction to air from process (initial release prior to RMM): 0.001
Emission factor - water Release fraction to wastewater from process (initial release prior to RMM): 0.000001
Emission factor - soil Release fraction to soil from process (initial release prior to RMM): 0.00001

Environmental factors not influenced by risk management measures

Dilution Local freshwater dilution factor: 10
 Local marine water dilution factor: 100

Risk management measures

Good practice Common practices vary across sites, thus conservative process release estimates used.
 Risk from environmental exposure is driven by freshwater sediment.

Technical onsite conditions and measures to reduce or limit discharges to air, water and soil

Air Treat air emission to provide a typical removal efficiency of 90%.
Water No wastewater treatment required.
Soil Do not apply industrial sludge to natural soils. Sludge should be incinerated, contained or reclaimed.

Conditions and measures related to external treatment of waste for disposal

Waste treatment External treatment and disposal of waste should comply with applicable local and/or national regulations.

Conditions and measures related to external recovery of waste

Recovery method External recovery and recycling of waste should comply with applicable local and/or national regulations.

2. Conditions of use affecting exposure (Workers - Health 1)

Product characteristics

Physical state Liquid With potential for aerosol generation
Vapour pressure Vapour pressure < 0.5 kPa at STP.
Concentration details Covers percentage substance in the product up to 100% (unless stated differently).

Frequency and duration of use

Covers daily exposures up to 8 hours (unless stated differently).

Other given operational conditions affecting workers exposure

Setting Assumes a good basic standard of occupational hygiene is implemented.
Temperature Assumes use at not more than 20°C above ambient temperature, unless stated differently.

Distribution of Substance

Organisational measures to prevent/limit releases, dispersion and exposure

Organisational measures General measures applicable to all activities Control any potential exposure using measures such as contained or enclosed systems, properly designed and maintained facilities and a good standard of general ventilation. Drain down systems and clear transfer lines prior to breaking containment. Drain down and flush equipment where possible prior to maintenance. Where there is potential for exposure: Ensure relevant staff are informed of the nature of exposure and aware of basic actions to minimise exposures; Ensure suitable personal protective equipment is available; Clear up spills and dispose of waste in accordance with regulatory requirements; monitor effectiveness of control measures; consider the need for health surveillance; identify and implement corrective actions. . General measures (skin irritants) Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent/minimise exposures and to report any skin problems that may develop.

Risk management measures

General exposures (closed systems)
Handle substance within a closed system.
.

General exposures (open systems)
Wear suitable gloves tested to EN374.
.

Process sampling
No other specific measures identified.
.

Laboratory activities
No other specific measures identified.
.

Bulk closed loading and unloading
Handle substance within a closed system.
Wear suitable gloves tested to EN374.
.

Bulk open loading and unloading
Wear suitable gloves tested to EN374.
.

Drum and small package filling
Wear suitable gloves tested to EN374.
.

Equipment cleaning and maintenance
Drain down and flush system prior to equipment break-in or maintenance.
Wear chemically-resistant gloves (tested to EN374) in combination with 'basic' employee training.
.

Storage
Handle substance within a closed system.

3. Exposure estimation (Environment 1)

Assessment method Used Petrorisk model. (Hydrocarbon Block Method)

Risk-driving RCR - air compartment driven $RCR(air) \leq 0.00013$ Risk-driving RCR - water compartment driven $RCR(water) \leq 0.0032$

4. Guidance to check compliance with the exposure scenario (Environment 1)

Distribution of Substance

Guidance is based on assumed operating conditions which may not be applicable to all sites, thus, scaling may be necessary to define appropriate site-specific risk management measures. Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination. Required removal efficiency for air can be achieved using onsite technologies, either alone or in combination. Further details on scaling and control technologies are provided in SpERC factsheet (<http://cefic.org/en/reach-for-industries-libraries.html>).

3. Exposure estimation (Health 1)

Assessment method

The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated

Available hazard data do not enable the derivation of a DNEL for dermal irritant effects. Available hazard data do not support the need for a DNEL to be established for other health effects. Qualitative approach used to conclude safe use.

4. Guidance to check compliance with the exposure scenario (Health 1)

Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented. Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

Exposure scenario

Use as a Fuel - Industrial

Identification

Product name	Fuel oil, no. 2
CAS number	68476-30-2
Version number	2017
Es reference	ES12a

1. Title of exposure scenario

Main title	Use as a Fuel - Industrial
Process scope	Covers the use as a fuel (or fuel additive) and includes activities associated with its transfer, use, equipment maintenance and handling of waste.
<u>Environment</u>	
Environmental release category	ERC7 Use of functional fluid at industrial site
SPERC	ESVOC SPERC 7.12a.v1
<u>Worker</u>	
Process category	<p>PROC1 Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions</p> <p>PROC2 Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions</p> <p>PROC3 Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition</p> <p>PROC8a Transfer of substance or mixture (charging and discharging) at non-dedicated facilities</p> <p>PROC8b Transfer of substance or mixture (charging and discharging) at dedicated facilities</p> <p>PROC16 Use of fuels</p>

2. Conditions of use affecting exposure (Industrial - Environment 1)

<u>Product characteristics</u>	Substance is complex UVCB. Predominantly hydrophobic.
--------------------------------	---

<u>Amounts used</u>	<p>Fraction of EU tonnage used in region: 0.1</p> <p>Regional use tonnage: 47 000 tonnes/year</p> <p>Fraction of Regional tonnage used locally: 1</p> <p>Annual site tonnage: 47 000 tonnes</p> <p>Maximum daily site tonnage: 160 tonne/day</p>
---------------------	--

<u>Frequency and duration of use</u>	<p>Continuous release.</p> <p>Emission days: 300 days/year</p>
--------------------------------------	--

Other given operational conditions affecting environmental exposure

Emission factor - air	Release fraction to air from process (initial release prior to RMM): 0.005
Emission factor - water	Release fraction to wastewater from process (initial release prior to RMM): 0.00001

Use as a Fuel - Industrial

Emission factor - soil Release fraction to soil from process (initial release prior to RMM): 0

Environmental factors not influenced by risk management measures

Dilution Local freshwater dilution factor: 10
Local marine water dilution factor: 100

Risk management measures

Good practice Common practices vary across sites, thus conservative process release estimates used.
Risk from environmental exposure is driven by freshwater sediment.

STP details Estimated substance removal from wastewater via domestic sewage treatment: 95.2%
Removal efficiency (total): 95.2%
Maximum allowable site tonnage (M_{safe}), based on release following total wastewater treatment removal: 880 tonne/day
Assumed domestic sewage treatment plant flow (m³/day): 2000.

Technical onsite conditions and measures to reduce or limit discharges to air, water and soil

Air Treat air emission to provide a typical removal efficiency of 95%.

Water Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of (%): ≥ 73.2. If discharging to domestic sewage treatment plant, no onsite wastewater treatment required.

Soil Do not apply industrial sludge to natural soils. Sludge should be incinerated, contained or reclaimed.

Conditions and measures related to external treatment of waste for disposal

Waste treatment Combustion emissions limited by required exhaust emission controls. Combustion emissions considered in regional exposure assessment. External treatment and disposal of waste should comply with applicable local and/or national regulations.

Conditions and measures related to external recovery of waste

Recovery method This substance is consumed during use and no waste of the substance is generated.

2. Conditions of use affecting exposure (Workers - Health 1)

Product characteristics

Physical state Liquid With potential for aerosol generation

Vapour pressure Vapour pressure < 0.5 kPa at STP.

Concentration details Covers percentage substance in the product up to 100% (unless stated differently).

Frequency and duration of use

Covers daily exposures up to 8 hours (unless stated differently).

Other given operational conditions affecting workers exposure

Setting Assumes a good basic standard of occupational hygiene is implemented.

Temperature Assumes use at not more than 20°C above ambient temperature, unless stated differently.

Organisational measures to prevent/limit releases, dispersion and exposure

Use as a Fuel - Industrial

Organisational measures

General measures applicable to all activities Control any potential exposure using measures such as contained or enclosed systems, properly designed and maintained facilities and a good standard of general ventilation. Drain down systems and clear transfer lines prior to breaking containment. Drain down and flush equipment where possible prior to maintenance. Where there is potential for exposure: Ensure relevant staff are informed of the nature of exposure and aware of basic actions to minimise exposures; Ensure suitable personal protective equipment is available; Clear up spills and dispose of waste in accordance with regulatory requirements; monitor effectiveness of control measures; consider the need for health surveillance; identify and implement corrective actions. . General measures (skin irritants) Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent/minimise exposures and to report any skin problems that may develop.

Risk management measures

Bulk transfers

Wear suitable gloves tested to EN374.

.

Drum/batch transfers

Wear suitable gloves tested to EN374.

.

Use as a fuel

(closed systems)

No other specific measures identified.

.

Equipment cleaning and maintenance

Drain down and flush system prior to equipment break-in or maintenance.

Wear chemically-resistant gloves (tested to EN374) in combination with 'basic' employee training.

.

Storage

Handle substance within a closed system.

3. Exposure estimation (Environment 1)

Assessment method

Used Petrorisk model. (Hydrocarbon Block Method)

Risk-driving RCR - air compartment driven $RCR(air) \leq 0.00054$

Risk-driving RCR - water compartment driven $RCR(water) \leq 0.18$

4. Guidance to check compliance with the exposure scenario (Environment 1)

Guidance is based on assumed operating conditions which may not be applicable to all sites, thus, scaling may be necessary to define appropriate site-specific risk management measures. Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination. Required removal efficiency for air can be achieved using onsite technologies, either alone or in combination. Further details on scaling and control technologies are provided in SpERC factsheet (<http://cefic.org/en/reach-for-industries-libraries.html>).

3. Exposure estimation (Health 1)

Assessment method

The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated

Use as a Fuel - Industrial

Available hazard data do not enable the derivation of a DNEL for dermal irritant effects.
Available hazard data do not support the need for a DNEL to be established for other health effects. Qualitative approach used to conclude safe use.

4. Guidance to check compliance with the exposure scenario (Health 1)

Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented. Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

Exposure scenario

Use as a Fuel - Professional

Identification

Product name	Fuel oil, no. 2
CAS number	68476-30-2
Version number	2017
Es reference	ES12b

1. Title of exposure scenario

Main title	Use as a Fuel - Professional
Process scope	Covers the use as a fuel (or fuel additive) and includes activities associated with its transfer, use, equipment maintenance and handling of waste.
<u>Environment</u>	
Environmental release category	ERC9a Widespread use of functional fluid (indoor) ERC9b Widespread use of functional fluid (outdoor)
SPERC	ESVOC SPERC 9.12b.v1
<u>Worker</u>	
Process category	PROC1 Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions PROC2 Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions PROC3 Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition PROC8a Transfer of substance or mixture (charging and discharging) at non-dedicated facilities PROC8b Transfer of substance or mixture (charging and discharging) at dedicated facilities PROC16 Use of fuels

2. Conditions of use affecting exposure (Industrial - Environment 1)

<u>Product characteristics</u>	Substance is complex UVCB. Predominantly hydrophobic.
--------------------------------	---

<u>Amounts used</u>	Fraction of EU tonnage used in region: 0.1 Regional use tonnage: 83 000 tonnes/year Fraction of Regional tonnage used locally: 0.0005 Annual site tonnage: 42 tonnes Maximum daily site tonnage: 0.11 tonne/day
---------------------	---

<u>Frequency and duration of use</u>	Continuous release. Emission days: 365 days/year
--------------------------------------	---

Other given operational conditions affecting environmental exposure

Emission factor - air	Release fraction to air from wide dispersive use (regional only): 0.0001
Emission factor - water	Release fraction to wastewater from wide dispersive use: 0.00001

Use as a Fuel - Professional

Emission factor - soil Release fraction to soil from wide dispersive use (regional only): 0.00001

Environmental factors not influenced by risk management measures

Dilution Local freshwater dilution factor: 10
Local marine water dilution factor: 100

Risk management measures

Good practice Common practices vary across sites, thus conservative process release estimates used.
Risk from environmental exposure is driven by fresh water.

STP details Estimated substance removal from wastewater via domestic sewage treatment: 95.2%
Removal efficiency (total): 95.2%
Maximum allowable site tonnage (M_{safe}), based on release following total wastewater treatment removal: 300 tonne/day
Assumed domestic sewage treatment plant flow (m³/day): 2000.

Technical onsite conditions and measures to reduce or limit discharges to air, water and soil

Air Not determined.

Water No wastewater treatment required.

Soil Do not apply industrial sludge to natural soils. Sludge should be incinerated, contained or reclaimed.

Conditions and measures related to external treatment of waste for disposal

Waste treatment Combustion emissions limited by required exhaust emission controls. Combustion emissions considered in regional exposure assessment. External treatment and disposal of waste should comply with applicable local and/or national regulations.

Conditions and measures related to external recovery of waste

Recovery method This substance is consumed during use and no waste of the substance is generated.

2. Conditions of use affecting exposure (Workers - Health 1)

Product characteristics

Physical state Liquid With potential for aerosol generation

Vapour pressure Vapour pressure < 0.5 kPa at STP.

Concentration details Covers percentage substance in the product up to 100% (unless stated differently).

Frequency and duration of use

Covers daily exposures up to 8 hours (unless stated differently).

Other given operational conditions affecting workers exposure

Setting Assumes a good basic standard of occupational hygiene is implemented.

Temperature Assumes use at not more than 20°C above ambient temperature, unless stated differently.

Organisational measures to prevent/limit releases, dispersion and exposure

Use as a Fuel - Professional

Organisational measures

General measures applicable to all activities Control any potential exposure using measures such as contained or enclosed systems, properly designed and maintained facilities and a good standard of general ventilation. Drain down systems and clear transfer lines prior to breaking containment. Drain down and flush equipment where possible prior to maintenance. Where there is potential for exposure: Ensure relevant staff are informed of the nature of exposure and aware of basic actions to minimise exposures; Ensure suitable personal protective equipment is available; Clear up spills and dispose of waste in accordance with regulatory requirements; monitor effectiveness of control measures; consider the need for health surveillance; identify and implement corrective actions. . General measures (skin irritants) Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent/minimise exposures and to report any skin problems that may develop.

Risk management measures

Bulk transfers

Wear suitable gloves tested to EN374.

.

Drum/batch transfers

Use drum pumps or carefully pour from container.

Wear suitable gloves tested to EN374.

.

Refuelling

Wear suitable gloves tested to EN374.

.

Use as a fuel

(closed systems)

Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour).

, or:

Ensure operation is undertaken outdoors.

.

Equipment cleaning and maintenance

Drain down and flush system prior to equipment break-in or maintenance.

Wear chemically-resistant gloves (tested to EN374) in combination with 'basic' employee training.

.

Storage

Handle substance within a closed system.

3. Exposure estimation (Environment 1)

Assessment method

Used Petrorisk model. (Hydrocarbon Block Method)

Risk-driving RCR - air compartment driven $RCR(air) \leq 0.00013$

Risk-driving RCR - water compartment driven $RCR(water) \leq 0.00038$

4. Guidance to check compliance with the exposure scenario (Environment 1)

Guidance is based on assumed operating conditions which may not be applicable to all sites, thus, scaling may be necessary to define appropriate site-specific risk management measures. Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination. Required removal efficiency for air can be achieved using onsite technologies, either alone or in combination. Further details on scaling and control technologies are provided in SpERC factsheet (<http://cefic.org/en/reach-for-industries-libraries.html>).

Use as a Fuel - Professional

3. Exposure estimation (Health 1)

Assessment method

The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated

Available hazard data do not enable the derivation of a DNEL for dermal irritant effects.
Available hazard data do not support the need for a DNEL to be established for other health effects. Qualitative approach used to conclude safe use.

4. Guidance to check compliance with the exposure scenario (Health 1)

Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented. Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.