



SAFETY DATA SHEET NESTE PRO 0W-30

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name	NESTE PRO 0W-30
Product number	ID 19021
Internal identification	1167
Synonyms; trade names	Previous product name: NESTE CITY PRO A5/B5 0W-30, product number 0137, ID 13945.

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Engine oil.

1.3. Details of the supplier of the safety data sheet

Supplier Neste Markkinointi Oy
Keilaranta 21, Espoo, P.O.B. 95, FIN-00095 NESTE, FINLAND
Tel. +358 10 45811
lubetec@neste.com

1.4. Emergency telephone number

National emergency telephone number +358-9-471 977, +358-9-4711, Poison Information Centre number

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards	Not Classified
Health hazards	Not Classified
Environmental hazards	Not Classified

2.2. Label elements

Hazard statements	EUH208 Contains C14-16-18 Alkyl phenol. May produce an allergic reaction.
Supplemental label information	EUH210 Safety data sheet available on request.

2.3. Other hazards

Other hazards Risk of soil and ground water contamination.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

NESTE PRO 0W-30

Distillates (petroleum), hydrotreated heavy paraffinic	70 - < 80 %
CAS number: 64742-54-7	EC number: 265-157-1
	REACH registration number: 01-2119484627-25-XXXX
Classification	
Asp. Tox. 1 - H304	
bis(nonylphenyl)amine	1 - < 2,5 %
CAS number: 36878-20-3	EC number: 253-249-4
	REACH registration number: 01-2119488911-28-XXXX
Classification	
Aquatic Chronic 4 - H413	
zinc bis[O-(6-methylheptyl)] bis[O-(sec-butyl)] bis(dithiophosphate)	1 - < 2,5 %
CAS number: 93819-94-4	EC number: 298-577-9
	REACH registration number: 01-2119543726-33-XXXX
Classification	
Skin Irrit. 2 - H315	
Eye Dam. 1 - H318	
Aquatic Chronic 2 - H411	
C14-16-18 Alkyl phenol	0,5 - < 1 %
CAS number: —	EC number: 931-468-2
	REACH registration number: 01-2119498288-19-XXXX
Classification	
Skin Sens. 1B - H317	
STOT RE 2 - H373	

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation	Remove person to fresh air and keep comfortable for breathing. Get medical attention if symptoms are severe or persist.
Ingestion	Rinse mouth. Do not induce vomiting unless under the direction of medical personnel. Never give anything by mouth to an unconscious person. Get medical attention if symptoms are severe or persist.
Skin contact	Remove contaminated clothing immediately and wash skin with soap and water.
Eye contact	Rinse immediately with plenty of water. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation persists after washing.

4.2. Most important symptoms and effects, both acute and delayed

General information	The product contains a small amount of sensitising substance. May cause an allergic skin reaction.
----------------------------	----------------------------------------------------------------------------------------------------

NESTE PRO 0W-30

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media Water spray, foam, dry powder or carbon dioxide.

Unsuitable extinguishing media Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Specific hazards None known.

Hazardous combustion products Carbon monoxide (CO). Carbon dioxide (CO₂). Hydrocarbons. Nitrous gases (NO_x). Zinc oxide fumes. Sulphurous gases (SO_x). Hydrogen sulphide (H₂S). Mercaptans.

5.3. Advice for firefighters

Protective actions during firefighting Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk. Contain and collect extinguishing water. Avoid discharge into drains.

Special protective equipment for firefighters Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Wear suitable protective clothing as protection against splashing or contamination.

For emergency responders Keep unnecessary and unprotected personnel away from the spillage.

6.2. Environmental precautions

Environmental precautions Stop leak if safe to do so. Avoid the spillage or runoff entering drains, sewers or watercourses. Contain spillage with sand, earth or other suitable non-combustible material. Inform the relevant authorities if environmental pollution occurs (sewers, waterways, soil or air).

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Absorb spillage with sand or other inert absorbent. Place waste in labelled, sealed containers. Dispose of waste via a licensed waste disposal contractor.

6.4. Reference to other sections

Reference to other sections For personal protection, see Section 8.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Avoid inhalation of vapours and spray/mists. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. All handling should only take place in well-ventilated areas. Take precautionary measures against static discharges. For personal protection, see Section 8.

Advice on general occupational hygiene Wash hands and any other contaminated areas of the body with soap and water before leaving the work site.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Store in tightly-closed, original container in a dry, cool and well-ventilated place. Keep containers upright. Keep away from food, drink and animal feeding stuffs.

NESTE PRO 0W-30

7.3. Specific end use(s)

Specific end use(s) Not known.

SECTION 8: Exposure controls/Personal protection

8.1. Control parameters

zinc bis[O-(6-methylheptyl)] bis[O-(sec-butyl)] bis(dithiophosphate) (CAS: 93819-94-4)

DNEL	<p>Workers - Inhalation; Long term systemic effects: 8,31 mg/m³</p> <p>Workers - Dermal; Long term systemic effects: 0,58 mg/kg</p> <p>Consumer - Inhalation; Long term systemic effects: 2,11 mg/m³</p> <p>Consumer - Dermal; Long term systemic effects: 0,29 mg/kg</p> <p>Consumer - Oral; Long term systemic effects: 0,24 mg/kg</p>
-------------	----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

8.2. Exposure controls

Appropriate engineering controls	All handling should only take place in well-ventilated areas. Provide eyewash station and safety shower.
Eye/face protection	Tight-fitting safety glasses.
Hand protection	Wear protective gloves. It is recommended that gloves are made of the following material: Nitrile rubber. Butyl rubber.
Other skin and body protection	Wear suitable protective clothing as protection against splashing or contamination.
Respiratory protection	No specific recommendations.
Environmental exposure controls	Store in a demarcated bunded area to prevent release to drains and/or watercourses.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	Liquid.
Colour	Tan.
Odour	Petroleum.
Odour threshold	-
pH	-
Melting point	< -45°C Pour point
Initial boiling point and range	> 350°C
Flash point	232°C Cleveland open cup.
Flammability (solid, gas)	-
Upper/lower flammability or explosive limits	-
Vapour pressure	-
Vapour density	-
Relative density	~ 0,842 @ 15°C
Solubility(ies)	Insoluble in water.

NESTE PRO 0W-30

Partition coefficient	-
Auto-ignition temperature	-
Decomposition Temperature	-
Viscosity	~ 51,9 mm ² /s @ 40°C Kinematic viscosity
Explosive properties	-
Oxidising properties	-

9.2. Other information

Other information Not known.

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity There are no known reactivity hazards associated with this product.

10.2. Chemical stability

Stability Stable at normal ambient temperatures and when used as recommended.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions No potentially hazardous reactions known.

10.4. Conditions to avoid

Conditions to avoid Avoid exposure to high temperatures or direct sunlight.

10.5. Incompatible materials

Materials to avoid Strong oxidising agents.

10.6. Hazardous decomposition products

Hazardous decomposition products No known hazardous decomposition products.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Toxicological effects Based on available data the classification criteria are not met.

Acute toxicity - oral

Notes (oral LD₅₀) LD₅₀ > 2000 mg/kg, Oral, Rat

Acute toxicity - dermal

Notes (dermal LD₅₀) LD₅₀ > 2000 mg/kg, Dermal, Rabbit

Skin corrosion/irritation

Skin corrosion/irritation Based on available data the classification criteria are not met.

Serious eye damage/irritation

Serious eye damage/irritation Based on available data the classification criteria are not met. Supplier's information. Bridging principle (Dilution).

Respiratory sensitisation

Respiratory sensitisation Based on available data the classification criteria are not met.

Skin sensitisation

NESTE PRO 0W-30

Skin sensitisation The product contains a small amount of sensitising substance. Based on available data the classification criteria are not met. Supplier's information. Bridging principle (Dilution).

Germ cell mutagenicity

Genotoxicity - in vivo Based on available data the classification criteria are not met.

Carcinogenicity

Carcinogenicity Based on available data the classification criteria are not met.

Reproductive toxicity

Reproductive toxicity - fertility Based on available data the classification criteria are not met.

Reproductive toxicity - development Based on available data the classification criteria are not met.

Specific target organ toxicity - single exposure

STOT - single exposure Based on available data the classification criteria are not met.

Specific target organ toxicity - repeated exposure

STOT - repeated exposure Based on available data the classification criteria are not met.

Aspiration hazard

Aspiration hazard Based on available data the classification criteria are not met.

Toxicological information on ingredients.

Distillates (petroleum), hydrotreated heavy paraffinic

Acute toxicity - oral

Notes (oral LD₅₀) LD₅₀ > 15000 mg/kg, Oral, Rat

Acute toxicity - dermal

Notes (dermal LD₅₀) LD₅₀ > 5000 mg/kg, Dermal, Rabbit

bis(nonylphenyl)amine

Acute toxicity - oral

Notes (oral LD₅₀) LD₅₀ > 5000 mg/kg, Oral, Rat

Acute toxicity - dermal

Notes (dermal LD₅₀) LD₅₀ > 2000 mg/kg, Dermal, Rat

zinc bis[O-(6-methylheptyl)] bis[O-(sec-butyl)] bis(dithiophosphate)

Acute toxicity - oral

Notes (oral LD₅₀) LD₅₀ 2600 mg/kg, Oral, Rat

Acute toxicity - dermal

Notes (dermal LD₅₀) LD₅₀ > 3160 mg/kg, Dermal, Rabbit (OECD TG 402)

C14-16-18 Alkyl phenol

Acute toxicity - oral

Notes (oral LD₅₀) LD₅₀ > 2000 mg/kg, Oral, Rat

Acute toxicity - dermal

Notes (dermal LD₅₀) LD₅₀ > 2000 mg/kg, Dermal, Rat

NESTE PRO 0W-30

SECTION 12: Ecological information

12.1. Toxicity

Toxicity The product is not expected to be hazardous to the environment. Based on available data the classification criteria are not met.

Ecological information on ingredients.

Distillates (petroleum), hydrotreated heavy paraffinic

Acute aquatic toxicity

Acute toxicity - fish	LL ₅₀ , 96 hours: > 100 mg/l,
Acute toxicity - aquatic invertebrates	EL ₅₀ , 48 hours: > 10000 mg/l,
Acute toxicity - aquatic plants	EL ₅₀ , 72 hours: > 100 mg/l,

Chronic aquatic toxicity

Chronic toxicity - fish early life stage	NOEC, : 10 mg/l,
Chronic toxicity - aquatic invertebrates	NOEC, : 10 mg/l,

bis(nonylphenyl)amine

Acute aquatic toxicity

Acute toxicity - fish	LC ₅₀ , 96 hours: > 100 mg/l, Brachydanio rerio (Zebra Fish)
Acute toxicity - aquatic invertebrates	EC ₅₀ , 48 hours: > 100 mg/l, Daphnia magna WAF
Acute toxicity - aquatic plants	EC ₅₀ , 72 hours: 600 mg/l, Pseudokirchneriella subcapitata

zinc bis[O-(6-methylheptyl)] bis[O-(sec-butyl)] bis(dithiophosphate)

Acute aquatic toxicity

Acute toxicity - fish	LL ₅₀ , 96 hours: 4,5 mg/l, Oncorhynchus mykiss (Rainbow trout)
Acute toxicity - aquatic invertebrates	EC ₅₀ , 48 hours: 5,4 mg/l, Daphnia magna
Acute toxicity - aquatic plants	EC ₅₀ , 72 hours: 2,1 mg/l, Selenastrum capricornutum

C14-16-18 Alkyl phenol

Acute aquatic toxicity

Acute toxicity - fish	LC ₅₀ , 96 hours: > 100 mg/l, Cyprinus carpio (Common carp) WAF
Acute toxicity - aquatic invertebrates	EC ₅₀ , 48 hours: > 100 mg/l, Daphnia magna (OECD TG 202)
Acute toxicity - aquatic plants	EC ₅₀ , 72 hours: > 100 mg/l, Pseudokirchneriella subcapitata WAF

NESTE PRO 0W-30

12.2. Persistence and degradability

Persistence and degradability No data available.

Biodegradation No data available.

Ecological information on ingredients.

bis(nonylphenyl)amine

Biodegradation 0 %, 28 d
(OECD TG 301 B)

zinc bis[O-(6-methylheptyl)] bis[O-(sec-butyl)] bis(dithiophosphate)

Biodegradation 1,5 %, 28 d
(OECD TG 301 B)

12.3. Bioaccumulative potential

Bioaccumulative potential No data available on bioaccumulation.

Partition coefficient -

Ecological information on ingredients.

bis(nonylphenyl)amine

Partition coefficient log Pow: > 7,5

zinc bis[O-(6-methylheptyl)] bis[O-(sec-butyl)] bis(dithiophosphate)

Partition coefficient log Pow 0,59 - 1,2 @ 23°C

C14-16-18 Alkyl phenol

Partition coefficient log Pow: > 7,2

12.4. Mobility in soil

Mobility No data available.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment No data available.

12.6. Other adverse effects

Other adverse effects Risk of soil and ground water contamination.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal methods Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority. Care should be taken when handling emptied containers that have not been thoroughly cleaned or rinsed out. Do not reuse empty containers.

SECTION 14: Transport information

General The product is not covered by international regulations on the transport of dangerous goods (IMDG, IATA, ADR/RID).

14.1. UN number

NESTE PRO 0W-30-
UN No. (ADR/RID) -**14.2. UN proper shipping name**Proper shipping name -
(ADR/RID)**14.3. Transport hazard class(es)**

ADR/RID class -

14.4. Packing group

ADR/RID packing group -

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

No.

14.6. Special precautions for user

Not applicable.

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78
and the IBC Code**SECTION 15: Regulatory information****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU legislation**Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended).
Commission Regulation (EU) No 2015/830 of 28 May 2015.
Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).**15.2. Chemical safety assessment**

No data available.

SECTION 16: Other information**Abbreviations and acronyms used in the safety data sheet** DNEL = Derived No-Effect Level
WAF = Water Accommodated Fraction**Key literature references and sources for data** The manufacturer's SDS. 22.8.2019**Revision comments** Revised formulation. Updated, sections: 3, 7, 9, 10 NOTE: Lines within the margin indicate significant changes from the previous revision.**Revision date** 11/09/2019**Supersedes date** 01/09/2017**SDS number** 4716

NESTE PRO 0W-30

Hazard statements in full

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H373 May cause damage to organs through prolonged or repeated exposure.

H411 Toxic to aquatic life with long lasting effects.

H413 May cause long lasting harmful effects to aquatic life.

EUH208 Contains C14-16-18 Alkyl phenol. May produce an allergic reaction.